



PNEUMAX®



PNEUMAX FLUID CONTROL

CATALOGUE

www.pneumaxspa.com



Pneumax Fluid Control Catalogue

Pneumax offers a wide range of brass and stainless steel valves and solenoid valves, suitable for use with liquid and gaseous fluids.





Pneumax Group

Smart Technologies and Human Competence

Founded in 1976, **Pneumax S.p.A.** is today one of the leading, international manufacturers of components and systems for automation. It is at the fore front of a group comprised of **27 companies**, with **over 800 employees worldwide**. Ongoing investment in research and development has allowed Pneumax to continually expand its range of standard products and customised solutions, adding to the well-established pneumatic technology, a range of electric drive actuators and fluid control components.

The desire to provide the service and specific application skills has led to the creation of 3 business units, dedicated to **Industrial Automation**, **Process Automation** and **Automotive sector**.

With the assistance of the specific Business unit Development Manager, Pneumax are able to design solutions than can add value to individual customer applications.



Pneumatic
technology



Electric
actuation



Fluid
control

Industrial automation



Process automation



Automotive



Components and systems for fluid control

The Pneumax range of components designed for the control and management of liquid and gaseous fluids have been manufactured using selected materials (valve bodies: brass, stainless steel, seals: FPM, PTFE & EPDM) in order to guarantee maximum reliability in harsh environments.

- **ATEX versions available**
- **Solutions for low temperatures ($>-40^{\circ}\text{C}$) or high temperatures ($<+140^{\circ}\text{C}$)**
- **Wide range of components suitable for use with oxygen**
- ** certified solenoid coils**

Pneumatic actuated angle seat valve



Pad valves



Servo-assisted piston and diaphragm solenoid valves



Direct acting poppet type solenoid valves



Index

Pneumax Fluid Control

Introduction

6

Direct acting poppet type solenoid valves 2/2 - 3/2 - Series F300

	F3105 - 2/2 Brass body - 1/8"	9		F3210 - 2/2 Stainless steel body - 1/4" ... 1/2"	22
	F3106 - 2/2 Brass body - 1/8" and 1/4"	10		F3211 - 2/2 Stainless steel body - 1/8"	23
	F3106 - 2/2 Stainless steel body - 3/8" and 1/2"	11		F3206 - 2/2 Brass body - 1/8" ... 1/2"	24 - 25
	FX3106 - 2/2 Brass body - 1/8" ... 1/2"	12 - 13		F3305 - 3/2 Brass body - 1/8"	26
	F3110 - 2/2 Stainless steel body - 1/4" ... 1/2"	14		F3306 - 3/2 Brass body - 1/8" and 1/4"	27
	FX3110 - 2/2 Stainless steel body - 1/4" ... 1/2"	15		F3310 - 3/2 Stainless steel body - 1/4"	28
	F3111 - 2/2 Stainless steel body - 1/8"	16		F3311 - 3/2 Stainless steel body - 1/8"	29
	F3115 - 2/2 Brass body - 1/8"	17		F332 - 3/2 Stainless steel body or anodised aluminium - 1/4"	30
	F3170 - 2/2 Stainless steel body - 1/4" ... 1/2"	18		F3371 - 3/2 Stainless steel body - 1/8"	31
	FX3170 - 2/2 Stainless steel body - 1/4" ... 1/2"	19		F3370 - 3/2 Stainless steel body - 1/4"	32
	F3171 - 2/2 Stainless steel body - 1/8"	20		FX3370 - 3/2 Stainless steel body - 1/4"	33
	F3271 - 2/2 Stainless steel body - 1/8"	21			

Servo-assisted diaphragm solenoid valves 2/2 - Series F300

	F3107 Brass body and cover 1/4" ... 3"	34 - 35		FX3177 Stainless steel body and cover 3/8" ... 1"	38
	FX3107 Brass body and cover 1/4" ... 3"	36		F3277 Stainless steel body and cover 3/8" ... 1"	39
	F3177 Stainless steel body and cover 3/8" ... 1"	37		F3207 Brass body and cover 1/4" ... 3"	40 - 41

Assisted-lift diaphragm solenoid valves 2/2 - Series F300

	F3108 Brass body and cover 3/8" ... 1"	42		FX3168 Brass body - 3/8" ... 1"	45
	F3168 Brass body and cover 3/8" ... 1" 1/2	43		FX3178 Stainless steel body - 3/8" ... 1"	46
	F3178 Stainless steel body and cover 3/8" ... 1" 1/2	44			

Servo-assisted piston solenoid valves 2/2 - Series F300

	F3119 Brass body and cover 1/4" ... 1/2"	47		F3124 Brass body and cover - 1/2"	50
	F3119W Brass body and cover 3/8" ... 1/2"	48		F3224 Brass body and cover - 1/2"	51
	F3123 Brass body and cover - 3/8"	49			

Solenoid coils - Series F300

	52
--	----

Pneumatic actuated angle seat valves 2/2 - Series PVF

	Connection type: threaded ports 1/2" ... 3"	53		Connection type: clamp ASME - BPE 56
	Connection type: welded connection	54		Connection type: flange mounting 57
	Connection type: clamp ISO 2852	55		Proximity sensor 58

Pad valves 2/2 - Series PVA

	"T" body version	59		"Y" body version	60
--	-------------------------	----	--	-------------------------	----



Series F300


General

F300 series includes a vast range of solenoid valves in brass and stainless steel designed to control air, water, steam and all fluids that are compatible with the materials used for bodies and seals. The solenoid valves are 2 or 3-way, normally closed, normally open, general service, direct acting or servo-assisted, with connections available in NPT & BSP threads from G1/8" up to G3", with a working pressure range from vacuum to 100 bar. Solenoid valves are available with coils that conform to CESI 03 ATEX 344 certification for explosive environments. Our technical office ensures the highest standard of skill and understanding for the widest variety of applications, ensuring that the best possible solutions are found.

Version manufactured


Solenoid valves direct action 2-ways: 2-way solenoid valves have an input connection and an output connection machined in the valve body, the orifice being intercepted by the poppet moved by the core tube.

They can be **normally closed (2/2 N.C.)**, in this case the fluid is intercepted by the poppet at rest, with electricity applied, the input orifice is opened and the media reaches the intended use.




They can be **normally open (2/2 N.O.)**, in this case at rest the orifice remains open without electricity applied, the media reaches the intended use. When electricity is applied the input orifice closes.

Performance in both cases depends solely on the magnetic field produced by the solenoid coil. The solenoid valves can also work at zero pressure.



Solenoid valves direct action 3-way: 3-way solenoid valves have an input and an output connection in the valve body and an exhaust connection fitted in the stem of the core tube. The input and exhaust orifices are intercepted directly by the poppet fitted within the core tube.

They can be **normally closed (3/2 N.C.)** and in this case, at rest, the incoming fluid is intercepted by the poppet and output port is connected to the exhaust port. Applying electrical power, the input orifice is opened and feed is supplied to the output. Exhaust is closed.




They can be **normally open (3/2 N.O.)** and in this case, at rest, the input orifice is open without electricity applied, the media reaches the intended use. Exhaust is closed.

Applying power, the input orifice closes and the output discharges through the exhaust port.

Performance in both cases depends solely on the magnetic field produced by the solenoid coil.

The solenoid valves can also work at zero pressure.



Servo-assisted solenoid valves


Large-sized passage orifices increase the value of the static pressure which has to be overcome by the magnetic field produced by the coil. These solenoid valves are used to control high-pressure values with large diameter bores. In these models, the fluid helps in the opening or closing of the main poppet.

They can be **normally closed (2/2 N.C.)** and have an input and a utilisation connection machined into the valve body and at rest the fluid is intercepted by the main poppet, which can be either diaphragm or a piston. In this condition, the fluid acts on both faces of the main plunger through a pinhole contributing to closure of the poppet.


Applying electrical power, the secondary, or pilot, orifice opens leading to the exhaust of the fluid, which acts to close the main poppet.

Greater force is thus applied when opening, the poppet is raised from the orifice and allows the media to flow to the output.

In these versions, performance does not depend solely on the magnetic field produced by the coil; a minimum input pressure is also needed so as to move the diaphragm or the piston overcoming its rigidity and to keep it raised from the main orifice (Δp minimum performance).



They can be **normally open (2/2 N.O.)** and have an input and output connection machined into the valve body, and at rest the core tube communicates with output, a minimum-pressure difference between the feed and the output causes the main poppet to rise, leading to its opening. Applying electrical power, the secondary orifice closes and equilibrium between the pressure on the two faces of the main poppet is reinstated, and so it returns to its closed position on the main orifice. In this version a minimum working pressure is also needed.



Sealing materials


Designation	Trade names	General characteristics	Field of use
FPM (Fluorocarbon)	VITON TECNOFLON FLUOREL	A synthetic hexa-fluoropropylene-based elastomer. Excellent resistance to high temperatures. Excellent resistance to ozone, oxygen, mineral oils, synthetic hydraulic fluids, fuels, hydrocarbons and many chemical products. Not specific for superheated steam.	For general use up to 140 °C

**Resistance to fluids**

The table below serves to general information relating to the compatibility between FPM (fluorocarbon) and a number of neutral fluids. Where there are corrosive fluids, in order to establish compatibility, it is important to be aware of all the data relating to use: temperature, concentration and composition of the fluid.

Fluid	
Ethyl acetate	Not compatible
Acetylene	Compatible
Vinegar	Not compatible
Acetone	Not compatible
Calcareous water	Compatible
Hot water <75 °C	Compatible
Hot water and steam <140 °C	Not compatible
Water with glycol	Compatible
Deionised water	Compatible
Demineralised water	Compatible
Hydrogen peroxide	Compatible
Soapy water	Compatible
Carbon dioxide (liquid)	Not compatible
Dry carbon dioxide (gas)	Compatible
Argon	Compatible
Nitrogen	Compatible
Petrol/Gasoline	Compatible
Benzol	Not compatible
Butane	Compatible
Chloroform	Not compatible
Ethyl Chloride	Compatible
Methyl chloride	Not compatible
Helium	Compatible
Heptane	Compatible
Hexane	Compatible
Ethane	Compatible
Ethanol	Not compatible
Formaldehyde	Compatible
Freon	Not compatible
Natural gas	Compatible
Diesel oil	Compatible
Glycerine	Compatible
Ethylene glycol	Compatible
Hydrogen	Compatible
Isobutane	Compatible
Isopentane	Compatible
Methane	Compatible
Methanol	Not compatible
Calcium monoxide	Compatible
Neon	Compatible
Nitrobenzene	Not compatible
Mineral oil	Compatible
Oxygen	Compatible
Pentane-n	Compatible
Propanol-n	Compatible
Propane-n	Compatible
Carbon sulphide	Not compatible
Toluene	Compatible
Dry trichloroethylene	Compatible
Xylene	Compatible

► F3105 - 2-way solenoid valve N.C. brass body, with G connection (ISO 228) - 1/8"




CODE "V" = FPM seals	G connection (ISO 228) Ⓐ = Connection	Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			Ⓑ = Solenoid coil	Temperature range (°C)
				Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)		
F3105CV12	A	1,2	0,04	0	25	25	12	6,5	MI	22
F3105CV15		1,5	0,06		16	16				
F3105CV20		2	0,09		12	10				
F3105CV25		2,5	0,14		8	5,5				
F3105CV31		3,1	0,19		5	2				
F3105CV40		4	0,35		4	1,5				

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3105CV25 → F3105AV25MI58:

2-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/8", FPM seals, orifice 2,5 mm, solenoid coil 230 VAC (50-60 Hz) (MI58, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body
- Brass guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):


- Manual override
- Chemical nickel plating surface treatment
- Stainless steel guide tube
- For use with oxygen
- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC
- FMus certified solenoid coils
- Versions for use with fluid temperature at -40 °C

Technical characteristics


Maximum admitted pressure (bar)	50
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Indifferent
Weight (g) with solenoid coil MI series	130
Weight (g) with solenoid coil MG series	180



► **F3106 - 2-way solenoid valve N.C. brass body, with G connection (ISO 228) - 1/8" and 1/4"**



The data in
brackets refer
to the MK Series coil




CODE "V"= FPM seals	G connection (ISO 228) Ⓐ= Connection		Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			Ⓑ= Solenoid coil	Temperature range (°C)				
	A	B			Min	Max		AC Inrush (VA)	AC Holding (VA)	DC (W)					
						AC	DC								
F3106CV10B	1/8"	1/4"	1	0,04	0	80	80	20	15	10	MG	30			
F3106CV12B			1,2	0,05		60	60								
F3106CV15B			1,5	0,07		30	26								
F3106CV20B			2	0,1		22	20								
F3106CV25B			2,5	0,15		16	14								
F3106CV30B			3	0,25		15	10								
F3106CV35B			3,5	0,32		10	8								
F3106CV40B			4	0,36		8	5								
F3106CV45B			4,5	0,41		6,5	3,5								
F3106CV52B		/	5,2	0,47		4	1,8								
F3106CV64B			6,4	0,64		3	1								
F3106CV10B	1/8"	1/4"	1	0,04		100	100	40	30	27	MK	36			
F3106CV12B			1,2	0,05		100	100								
F3106CV15B			1,5	0,07		80	80								
F3106CV20B			2	0,1		50	40								
F3106CV25B			2,5	0,15		35	33								
F3106CV30B			3	0,25		25	24								
F3106CV35B			3,5	0,32		20	19								
F3106CV40B			4	0,36		16	15								
F3106CV45B			4,5	0,41		14	13								
F3106CV52B		/	5,2	0,47		10	9								
F3106CV64B			6,4	0,64		5	4,5								

N.B. For use with steam, maximum admitted pressure PS is 9 bar (relative pressure) with seals in PTFE and 2.5 bar with seals in EPDM.


Example: F3106CV52B => F3106BV52MG58:

2-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/4", FPM seals, 5,2 mm orifice, solenoid coil 230 VAC (50-60 Hz) (MG58, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies


OPTIONS (on request):

- Manual override
- Chemical nickel plating surface treatment
- Stainless steel seat insert (up to Ø4,5)
- For use with oxygen
- certified solenoid coils
- Versions for use with fluid temperature at -40 °C
- PTFE - EPDM seals

Technical characteristics

Maximum admitted pressure (bar)	100
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80
Mounting position	Indifferent
Weight (g) with solenoid coil MG series	300
Weight (g) with solenoid coil MK series	380

F3106 - 2-way solenoid valve N.C. brass body, with G connection (ISO 228) - 3/8" and 1/2"




CODE "V" = FPM seals	G connection (ISO 228)		Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			B = Solenoid coil	Temperature range (°C)
	C	D			Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)		
	AC	DC									
F3106CV10@	3/8"	1/2"	1	0,04	0	80	80	20	10	MG	30
F3106CV12@			1,2	0,05		60	60				
F3106CV15@			1,5	0,07		30	26				
F3106CV20@			2	0,1		22	20				
F3106CV25@			2,5	0,15		16	14				
F3106CV30@			3	0,25		15	10				
F3106CV35@			3,5	0,32		10	8				
F3106CV40@			4	0,36		8	5				
F3106CV45@			4,5	0,41		6,5	3,5				
F3106CV52@			5,2	0,47		4	1,8				
F3106CV64@			6,4	0,64		3	1				
F3106CV10@	3/8"	1/2"	1	0,04		100	100	40	27	MK	36
F3106CV12@			1,2	0,05		100	100				
F3106CV15@			1,5	0,07		80	80				
F3106CV20@			2	0,1		50	40				
F3106CV25@			2,5	0,15		35	33				
F3106CV30@			3	0,25		25	24				
F3106CV35@			3,5	0,32		20	19				
F3106CV40@			4	0,36		16	15				
F3106CV45@			4,5	0,41		14	13				
F3106CV52@			5,2	0,47		10	9				
F3106CV64@			6,4	0,64		5	4,5				

N.B. For use with steam, maximum admitted pressure PS is 9 bar (relative pressure) with seals in PTFE and 2.5 bar with seals in EPDM.


Example: F3106CV52@ => F3106DV52MK5:

2-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/2", FPM seals, 5,2 mm orifice, solenoid coil 24 VDC (MK5, size 36 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):


- Chemical nickel plating surface treatment
- For use with oxygen
- Stainless steel seat insert (up to Ø4,5)
- CSA certified solenoid coils
- Versions for use with fluid temperature at -40 °C
- PTFE - EPDM seals

Technical characteristics

Maximum admitted pressure (bar)	100
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80
Mounting position	Indifferent
Weight (g) with solenoid coil MG series	360
Weight (g) with solenoid coil MK series	440



► **FX3106 - 2-way solenoid valve N.C. brass body, with G connection (ISO 228)
with certified housing: Ex d IIC T6 or T5 or T4 Gb - 1/8" and 1/4"**




CODE "V"= FPM seals	G connection (ISO 228) Ⓐ= Connection		Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption		Ⓐ= Solenoid coil	Temperature range (°C)
	A	B			Min	Max	AC Holding (VA)	DC (W)		
FX3106CV10Ⓐ	1/8"	1/4"	1	0,04	0	80	80	12	8	A6B= 24 Volt (AC 50-60 Hz) A6E= 220/230 Volt (AC 50-60 Hz) A60= 12 Volt (DC) A61= 24 Volt (DC)
FX3106CV12Ⓐ			1,2	0,05		60	60			
FX3106CV15Ⓐ			1,5	0,07		30	26			
FX3106CV20Ⓐ			2	0,1		22	20			
FX3106CV25Ⓐ			2,5	0,15		16	14			
FX3106CV30Ⓐ			3	0,25		15	10			
FX3106CV35Ⓐ			3,5	0,32		10	8			
FX3106CV40Ⓐ	/		4	0,36		8	5			
FX3106CV45Ⓐ	/		4,5	0,41		6,5	3,5			
FX3106CV52Ⓐ	/		5,2	0,47		4	1,8			
FX3106CV64Ⓐ	/		6,4	0,64		3	1			

N.B. The solenoid valve is suited for intercepting only fluids that are NOT potentially explosive.


Example: FX3106CV35Ⓐ => FX3106BV35A60:

2-way solenoid valve normally closed, direct acting poppet type with certified housing: Ex d IIC T6 or T5 or T4 Gb, with G connection (ISO 228) 1/4", FPM seals, 3,5 mm orifice, solenoid coil 12 VDC (A60).

Pneumatic symbol



Diagram



Construction characteristics

- Brass body
- Red light alloy housing
- 1/2" NPT electrical connection (M20x1,5 on request)
- FPM sealing assemblies


OPTIONS (on request):

- Manual override
- Chemical nickel plating surface treatment
- Stainless steel seat insert (up to Ø4,5)
- Stainless steel solenoid coil housing

Technical characteristics

Maximum admitted pressure (bar)	100
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature (°C)	-40 ... +60
Mounting position	Vertical with solenoid coil upwards
Weight (g)	600

► FX3106 - 2-way solenoid valve N.C. brass body, with G connection (ISO 228)
with certified housing: Ex d IIC T6 or T5 or T4 Gb - 3/8 and "1/2"




CODE "V" = FPM seals	G connection (ISO 228)		Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption		B = Solenoid coil	Temperature range (°C)			
	@= Connection				Min	Max		AC Holding (VA)	DC (W)				
	C	D				AC	DC						
FX3106CV10B	3/8"	1/2"	1	0,04	0	80	80	12	8	A6B= 24 Volt (AC 50-60 Hz) A6E= 220/230 Volt (AC 50-60 Hz) A60= 12 Volt (DC) A61= 24 Volt (DC)			
FX3106CV12B			1,2	0,05		60	60						
FX3106CV15B			1,5	0,07		30	26						
FX3106CV20B			2	0,1		22	20						
FX3106CV25B			2,5	0,15		16	14						
FX3106CV30B			3	0,25		15	10						
FX3106CV35B			3,5	0,32		10	8						
FX3106CV40B			4	0,36		8	5						
FX3106CV45B			4,5	0,41		6,5	3,5						
FX3106CV52B			5,2	0,47		4	1,8						
FX3106CV64B			6,4	0,64		3	1						

N.B. The solenoid valve is suited for intercepting only fluids that are NOT potentially explosive.


Example: FX3106CV52B => FX3106DV52A60:

2-way solenoid valve normally closed, direct acting poppet type with certified housing: Ex d IIC T6 or T5 or T4 Gb, with G connection (ISO 228) 1/2", FPM seals, 5,2 mm orifice, solenoid coil 12 VDC (A60).

Pneumatic symbol



Diagram



Construction characteristics

- Brass body
- Red light alloy housing
- 1/2" NPT electrical connection (M20x1,5 on request)
- FPM sealing assemblies

OPTIONS (on request):


- Chemical nickel plating surface treatment
- Stainless steel seat insert (up to Ø4,5)
- Stainless steel solenoid coil housing

Technical characteristics

Maximum admitted pressure (bar)	100
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature (°C)	-40 ... +60
Mounting position	Vertical with solenoid coil upwards
Weight (g)	660



► **F3110 - 2-way solenoid valve N.C. stainless steel body, with G connection (ISO 228) - 1/4" ... 1/2"**




CODE "V" = FPM seals	G connection (ISO 228) ◎ = Connection			Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			◎ = Solenoid coil	Temperature range (°C)				
	B	C	D			Min	Max		AC Inrush (VA)	AC Holding (VA)	DC (W)					
							AC	DC								
F3110CV10◎				1	0,04	80	80									
F3110CV12◎				1,2	0,05	60	60									
F3110CV15◎				1,5	0,07	30	26									
F3110CV20◎				2	0,1	22	20									
F3110CV25◎				2,5	0,15	16	14									
F3110CV30◎				3	0,25	15	10	20	15	10	MG	30				
F3110CV35◎				3,5	0,32	10	8									
F3110CV40◎				4	0,36	8	5									
F3110CV45◎				4,5	0,41	6,5	3,5									
F3110CV52◎				5,2	0,47	4	1,8									
F3110CV64◎				6,4	0,64	3	1									
F3110CV10◎				1	0,04	100	100						-10 ... +140			
F3110CV12◎				1,2	0,05	100	100									
F3110CV15◎				1,5	0,07	80	80									
F3110CV20◎				2	0,1	50	40									
F3110CV25◎				2,5	0,15	35	33									
F3110CV30◎				3	0,25	25	24	40	30	27	MK	36				
F3110CV35◎				3,5	0,32	20	19									
F3110CV40◎				4	0,36	16	15									
F3110CV45◎				4,5	0,41	14	13									
F3110CV52◎				5,2	0,47	10	9									
F3110CV64◎				6,4	0,64	5	4,5									

N.B. For use with steam, maximum admitted pressure PS is 9 bar (relative pressure) with seals in PTFE and 2.5 bar with seals in EPDM.


Example: F3110CV25◎ => F3110BV25MG5:

2-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/4", FPM seals, 2,5 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- AISI 303 stainless steel body
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies


OPTIONS (on request):

- Silver advance ring
- For use with oxygen
- certified solenoid coils
- Versions for use with fluid temperature at -40 °C
- PTFE - EPDM seals

Technical characteristics

Maximum admitted pressure (bar)	100
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80
Mounting position	Indifferent
Weight (g) with solenoid coil MG series	360
Weight (g) with solenoid coil MK series	440

► FX3110 - 2-way solenoid valve N.C. stainless steel body, with G connection (ISO 228)
with certified housing: Ex d IIC T6 or T5 or T4 Gb - 1/4" ... 1/2"




CODE "V" = FPM seals	G connection (ISO 228)			Orifice (mm)	KV (m³/h)	Differential pressure (bar)			Power consumption			④ = Solenoid coil	Temperature range (°C)				
	B	C	D			Min	Max		AC Holding (VA)	DC (W)							
							AC	DC									
FX3110CV10④	1/4"	3/8"	1/2"	1	0,04	0	80	80	12	8	A6B= 24 Volt (AC 50-60 Hz) A6E= 220/230 Volt (AC 50-60 Hz) A60= 12 Volt (DC) A61= 24 Volt (DC)	-10 ... +80					
FX3110CV12④				1,2	0,05		60	60									
FX3110CV15④				1,5	0,07		30	26									
FX3110CV20④				2	0,1		22	20									
FX3110CV25④				2,5	0,15		16	14									
FX3110CV30④				3	0,25		15	10									
FX3110CV35④				3,5	0,32		10	8									
FX3110CV40④				4	0,36		8	5									
FX3110CV45④				4,5	0,41		6,5	3,5									
FX3110CV52④				5,2	0,47		4	1,8									
FX3110CV64④				6,4	0,64		3,5	1									

N.B. The solenoid valve is suited for intercepting only fluids that are NOT potentially explosive.


Example: FX3110CV52④ => FX3110DV52A60:

2-way solenoid valve normally closed, direct acting poppet type with certified housing: Ex d IIC T6 or T5 or T4 Gb, with G connection (ISO 228) 1/2", FPM seals, 5,2 mm orifice, solenoid coil 12 VDC (A60).

Pneumatic symbol



Diagram



Construction characteristics


- AISI 303 stainless steel body
- AISI 303 stainless steel guide tube
- AISI 302 stainless steel springs
- Red light alloy or stainless steel housing
- 1/2" NPT electrical connection (M20x1,5 on request)
- FPM sealing assemblies

Technical characteristics

Maximum admitted pressure (bar)	100
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature (°C)	-40 ... +60
Mounting position	Vertical with solenoid coil upwards
Weight (g)	660



► **F3111 - 2-way solenoid valve N.C. stainless steel body, with G connection (ISO 228) - 1/8"**




CODE "V" = FPM seals	G connection (ISO 228) Ⓐ = Connection A	Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			Ⓑ = Solenoid coil Series	Temperature range (°C)
				Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)		
AC	DC									
F3111ⒶV12Ⓑ	1/8"	1,2	0,04	0	25	25	12	6,5	MI	-10 ... +140
F3111ⒶV15Ⓑ		1,5	0,06		16	16				
F3111ⒶV20Ⓑ		2	0,09		12	10				
F3111ⒶV25Ⓑ		2,5	0,14		8	5,5				
F3111ⒶV31Ⓑ		3,1	0,19		5	2				
F3111ⒶV20Ⓑ	1/8"	2	0,09	15	25	15	11	5	MG	30
F3111ⒶV25Ⓑ		2,5	0,14		16	8				
F3111ⒶV31Ⓑ		3,1	0,19		8	4				

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3111ⒶV25Ⓑ => F3111AV25MI8:

2-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/8", FPM seals, 2,5 mm orifice, solenoid coil 230 VAC (50-60 Hz) (MI8, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram




Construction characteristics	Technical characteristics
- AISI 303 stainless steel body	Maximum admitted pressure (bar) 50
- AISI 303 stainless steel guide tube	Maximum fluid viscosity (mm²/s) 25cSt
- AISI 430FR stainless steel mobile and fixed core	Ambient temperature: with class F solenoid coil (°C) -10 ... +55
- AISI 302 stainless steel springs	Mounting position Indifferent
- FPM sealing assemblies	Weight (g) with solenoid coil MI series 150
OPTIONS (on request):	Weight (g) with solenoid coil MG series 200
- Silver advance ring	
- For use with oxygen	
- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC	
- certified solenoid coils	
- Versions for use with fluid temperature at -40 °C	

► F3115 - 2-way solenoid valve brass body, with G connection (ISO 228) bistable impulse drive - 1/8"




The bistable function is achieved by the use of a polarized permanent magnet energizing the coil with a DC current for at least 15ms in the reverse direction of the preceding impulse.




CODE "V" = FPM seals	G connection (ISO 228) ◎ = Connection	Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption	◎ = Solenoid coil	Temperature range (°C)
				Min	Max			
F3115CV12◎	1/8"	1,2	0,04	0	12	2	MI/DC	22
F3115CV15◎		1,5	0,06		8	2		
F3115CV20◎		2	0,09		20	5		
F3115CV25◎		2,5	0,14		3	2		
F3115CV31◎		3,1	0,19		12	5		
					1	2		
					5	5		
					8	6,5		
					2	5		
					3,5	6,5		

Example: F3115◎V25◎ => F3115AV25MI5:
2-way solenoid valve, direct acting poppet type with G connection (ISO 228) 1/8", FPM seals, 2,5 mm orifice, solenoid coil 24 VDC (MI5, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol




Diagram



Construction characteristics	Technical characteristics
- Brass body - Brass guide tube - AISI 430FR stainless steel mobile and fixed core - AISI 302 stainless steel springs - FPM sealing assemblies	Maximum admitted pressure (bar) 50
OPTIONS (on request): - Chemical nickel plating surface treatment - Stainless steel guide tube - XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC	Maximum fluid viscosity (mm²/s) 25cSt
	Ambient temperature: with class F solenoid coil (°C) -10 ... +55
	Mounting position Indifferent
	Weight (g) 140



► **F3170 - 2-way solenoid valve N.C. stainless steel body, with G connection (ISO 228) - 1/4" ... 1/2"**



The data in
brackets refer to
the MK Series coil


CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection			Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			◎= Solenoid coil	Temperature range (°C)				
	B	C	D			Min	Max		AC Inrush (VA)	AC Holding (VA)	DC (W)					
							AC	DC								
F3170CV10◎	1/4"	3/8"	1/2"	1	0,04	0	80	80	20	15	10	MG	30			
F3170CV12◎				1,2	0,05		60	60								
F3170CV15◎				1,5	0,07		30	26								
F3170CV20◎				2	0,1		22	20								
F3170CV25◎				2,5	0,15		16	14								
F3170CV30◎				3	0,25		15	10								
F3170CV35◎				3,5	0,32		10	8								
F3170CV40◎				4	0,36		8	5								
F3170CV45◎				4,5	0,41		6,5	3,5								
F3170CV10◎	1/4"	3/8"	1/2"	1	0,04		100	100	40	30	27	MK	36			
F3170CV12◎				1,2	0,05		100	100								
F3170CV15◎				1,5	0,07		80	80								
F3170CV20◎				2	0,1		50	40								
F3170CV25◎				2,5	0,15		35	33								
F3170CV30◎				3	0,25		25	24								
F3170CV35◎				3,5	0,32		20	19								
F3170CV40◎				4	0,36		16	15								
F3170CV45◎				4,5	0,41		14	13								

N.B. For use with steam, maximum admitted pressure PS is 9 bar (relative pressure) with seals in PTFE and 2.5 bar with seals in EPDM.


Example: F3170CV25◎ => F3170BV25MG5:

2-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/4", FPM seals, 2,5 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- AISI 316 stainless steel body
- AISI 316 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 316 stainless steel springs
- Silver advance ring
- FPM sealing assemblies

OPTIONS (on request):



- For use with oxygen
- certified solenoid coils
- Versions for use with fluid temperature at -40 °C
- PTFE - EPDM seals

Technical characteristics

Maximum admitted pressure (bar)	100
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80
Mounting position	Indifferent
Weight (g) with solenoid coil MG series	360
Weight (g) with solenoid coil MK series	440



► FX3170 - 2-way solenoid valve N.C. stainless steel body, with G connection (ISO 228)
with certified housing: Ex d IIC T6 or T5 or T4 Gb - 1/4" ... 1/2"




CODE "V" = FPM seals	G connection (ISO 228)			Orifice (mm)	KV (m³/h)	Differential pressure (bar)			Power consumption			B = Solenoid coil	Temperature range (°C)				
	B	C	D			Min	Max		AC Holding (VA)	DC (W)							
							AC	DC									
FX3170CV10B	1/4"	3/8"	1/2"	1	0,04	0	80	80	12	8	A6B= 24 Volt (AC 50-60 Hz) A6E= 220/230 Volt (AC 50-60 Hz) A60= 12 Volt (DC) A61= 24 Volt (DC)	-10 ... +80					
FX3170CV12B				1,2	0,05		60	60									
FX3170CV15B				1,5	0,07		30	26									
FX3170CV20B				2	0,1		22	20									
FX3170CV25B				2,5	0,15		16	14									
FX3170CV30B				3	0,25		15	10									
FX3170CV35B				3,5	0,32		10	8									
FX3170CV40B				4	0,36		8	5									
FX3170CV45B				4,5	0,41		6,5	3,5									

N.B. The solenoid valve is suited for intercepting only fluids that are NOT potentially explosive.


Example: FX3170CV45B => FX3170DV45A60:

2-way solenoid valve normally closed, direct acting poppet type with certified housing: Ex d IIC T6 or T5 or T4 Gb, with G connection (ISO 228) 1/2", FPM seals, 4,5 mm orifice, solenoid coil 12 VDC (A60).

Pneumatic symbol



Diagram



Construction characteristics


- AISI 316 stainless steel body
- AISI 316 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- Silver advance ring
- AISI 316 stainless steel springs
- Red light alloy or stainless steel housing
- 1/2" NPT electrical connection (M20x1,5 on request)
- FPM sealing assemblies

Technical characteristics

Maximum admitted pressure (bar)	100
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature (°C)	-40 ... +60
Mounting position	Vertical with solenoid coil upwards
Weight (g)	660



► **F3171 - 2-way solenoid valve N.C. stainless steel body, with G connection (ISO 228) - 1/8"**




CODE "V" = FPM seals	G connection (ISO 228) Ⓐ = Connection	Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			Ⓑ = Solenoid coil	Temperature range (°C)
				Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)		
	A			AC	DC					
F3171CV12B	1/8"	1,2	0,04	0	25	25	12	8	MI	22
F3171CV15B		1,5	0,06		16	16				
F3171CV20B		2	0,09		12	10				
F3171CV25B		2,5	0,14		8	5,5				
F3171CV31B		3,1	0,19		5	2				
F3171CV20B		2	0,09		25	15	15	11	MG	30
F3171CV25B		2,5	0,14		16	8				
F3171CV31B		3,1	0,19		8	4				

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3171CV25B => F3171AV25MI58:

2-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/8", FPM seals, 2,5 mm orifice, solenoid coil 230 VAC (50-60 Hz) (MI58, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- AISI 316 stainless steel body
- AISI 316 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- Silver advance ring
- AISI 316 stainless steel springs
- FPM sealing assemblies


OPTIONS (on request):

- For use with oxygen
- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC
- cULus certified solenoid coils
- Versions for use with fluid temperature at -40 °C

Technical characteristics

Maximum admitted pressure (bar)	50
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Indifferent
Weight (g) with solenoid coil MI series	150
Weight (g) with solenoid coil MG series	200

► F3271 - 2-way solenoid valve N.O. stainless steel body, with G connection (ISO 228) - 1/8"




CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection A	Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			◎= Solenoid coil	Temperature range (°C)
				Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)		
F3271◎V12◎	1/8"	1,2	0,04	0	19	19	12	6,5	MI	-10 ... +140
F3271◎V15◎		1,5	0,06		14	14				
F3271◎V20◎		2	0,09		8	8				
F3271◎V25◎		2,5	0,14		4,5	4,5				
F3271◎V31◎		3,1	0,19		2,5	2,5				

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3271◎V25◎ => F3271AV25MI58:

2-way solenoid valve normally open, direct acting poppet type with G connection (ISO 228) 1/8", FPM seals, 2,5 mm orifice, solenoid coil 230 VAC (50-60 Hz) (MI58, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- AISI 316 stainless steel body
- AISI 316 stainless steel tube
- AISI 430R stainless steel mobile and fixed core
- Silver advance ring
- AISI 316 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):


- For use with oxygen
- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC
- FMus certified solenoid coils
- Versions for use with fluid temperature at -40 °C

Technical characteristics

Maximum admitted pressure (bar)	50
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Indifferent
Weight (g)	150



► **F3210 - 2-way solenoid valve N.O. stainless steel body, with G connection (ISO 228) - 1/4" ... 1/2"**




CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection			Orifice (mm)	KV (m³/h)	Differential pressure (bar)			Power consumption			◎= Solenoid coil	Temperature range (°C)									
	B	C	D			Min	Max		AC Inrush (VA)	AC Holding (VA)	DC (W)											
F3210CV15◎				1,5	0,07		23	/														
				2	0,1		17															
				2,5	0,15		12															
				3	0,25		9															
				3,5	0,32		7															
				4	0,36		5,5															
				4,5	0,41		4,5															
				5,2	0,47		3															
F3210CV15◎	1/4"	3/8"	1/2"	1,5	0,07	0	18	/	20	15	/	MG/AC	30									
				2	0,1		11															
				2,5	0,15		7															
				3	0,25		6,5															
				3,5	0,32		4															
				4	0,36		3,5															
				4,5	0,41		3															
				5,2	0,47		2,2															
				6,4	0,64		23															
				1,5	0,07		17															
F3210CV15◎	1/4"	3/8"	1/2"	2	0,1		12															
				2,5	0,15		9															
				3	0,25		7															
				3,5	0,32		6,5															
				4	0,36		4															
				4,5	0,41		3,5															
				5,2	0,47		3															
				6,4	0,64		3,5															
				1,5	0,07		23															
				2	0,1		17															
F3210CV15◎	1/4"	3/8"	1/2"	2,5	0,15		12															
				3	0,25		9															
				3,5	0,32		7															
				4	0,36		5,5															
				4,5	0,41		4,5															
				5,2	0,47		3															
				6,4	0,64		3,5															
				1,5	0,07		23															
				2	0,1		17															
				2,5	0,15		12															

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3210CV25◎ => F3210BV25MG5:

2-way solenoid valve normally open, direct acting poppet type with G connection (ISO 228) 1/4", FPM seals, 2,5 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- AISI 303 stainless steel body
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies


OPTIONS (on request):

- Silver advance ring
- For use with oxygen
- Certified solenoid coils
- Versions for use with fluid temperature at -40 °C
- Manual override

Technical characteristics

Maximum admitted pressure (bar)	50
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80
Mounting position	Indifferent
Weight (g) with solenoid coil MG series	300
Weight (g) with solenoid coil MK series	380

► F3211 - 2-way solenoid valve N.O. stainless steel body, with G connection (ISO 228) - 1/8"




CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection A	Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			◎= Solenoid coil	Temperature range (°C)
				Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)		
F3211◎V12◎	1/8"	1,2	0,04	0	19	19	12	6,5	MI	-10 ... +140
F3211◎V15◎		1,5	0,06		14	14				
F3211◎V20◎		2	0,09		8	8				
F3211◎V25◎		2,5	0,14		4,5	4,5				
F3211◎V31◎		3,1	0,19		2,5	2,5				

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3211◎V25◎ => F3211AV25MI58:

2-way solenoid valve normally open, direct acting poppet type with G connection (ISO 228) 1/8", FPM seals, 2,5 mm orifice, solenoid coil 230 VAC (50-60 Hz) (MI58, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- AISI 303 stainless steel body
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):


- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC
- For use with oxygen
- FM us certified solenoid coils
- Versions for use with fluid temperature at -40 °C
- Manual override

Technical characteristics

Maximum admitted pressure (bar)	50
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Indifferent
Weight (g)	150



► **F3206 - 2-way solenoid valve N.O. brass body, with G connection (ISO 228) - 1/8" and 1/4"**




CODE "V" = FPM seals	G connection (ISO 228) ◎ = Connection		Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			◎ = Solenoid coil	Temperature range (°C)				
	A	B			Min	Max		AC Inrush (VA)	AC Holding (VA)	DC (W)					
						AC	DC								
F3206CV15◎	1/8"	1/4"	1,5	0,07	0	23	/	20	15	/	MG/AC	30			
F3206CV20◎			2	0,1		17									
F3206CV25◎			2,5	0,15		12									
F3206CV30◎			3	0,25		8									
F3206CV35◎			3,5	0,32		7									
F3206CV40◎			4	0,36		5,5									
F3206CV45◎			4,5	0,41		4,5									
F3206CV52◎			5,2	0,47		3									
F3206CV15◎	1/8"	1/4"	1,5	0,07	0	18	/	/	10	MG/DC	30	-10 ... +140			
F3206CV20◎			2	0,1		11									
F3206CV25◎			2,5	0,15		7									
F3206CV30◎			3	0,25		6,5									
F3206CV35◎			3,5	0,32		4									
F3206CV40◎			4	0,36		3,5									
F3206CV45◎			4,5	0,41		3									
F3206CV52◎			5,2	0,47		2,2									
F3206CV15◎	1/8"	1/4"	1,5	0,07	40	23	23	30	27	MK (AC/DC)	36				
F3206CV20◎			2	0,1		17									
F3206CV25◎			2,5	0,15		12									
F3206CV30◎			3	0,25		8									
F3206CV35◎			3,5	0,32		7									
F3206CV40◎			4	0,36		5,5									
F3206CV45◎			4,5	0,41		4,5									
F3206CV52◎			5,2	0,47		3									
F3206CV64◎			6,4	0,64		3,5									

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3206CV25◎ => F3206BV25MG5:

2-way solenoid valve normally open, direct acting poppet type with G connection (ISO 228) 1/4", FPM seals, 2,5 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body
- Brass guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):


- Stainless steel guide tube
- Chemical nickel plating surface treatment
- cULus certified solenoid coils
- Versions for use with fluid temperature at -40 °C
- Manual override

Technical characteristics

Maximum admitted pressure (bar)	50
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80
Mounting position	Indifferent
Weight (g) with solenoid coil MG series	300
Weight (g) with solenoid coil MK series	380



► F3206 - 2-way solenoid valve N.O. brass body, with G connection (ISO 228) - 3/8" and 1/2"




CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection		Orifice (mm)	KV (m³/h)	Differential pressure (bar)			Power consumption			◎= Solenoid coil	Temperature range (°C)				
	C	D			Min	Max		AC Inrush (VA)	AC Holding (VA)	DC (W)						
						AC	DC									
F3206CV15◎	3/8"	1/2"	1,5	0,07	23			20	15	/	MG/AC	30				
F3206CV20◎			2	0,1	17											
F3206CV25◎			2,5	0,15	12											
F3206CV30◎			3	0,25	9											
F3206CV35◎			3,5	0,32	7											
F3206CV40◎			4	0,36	5,5											
F3206CV45◎			4,5	0,41	4,5											
F3206CV52◎			5,2	0,47	3											
F3206CV15◎	3/8"	1/2"	1,5	0,07	18			/	/	10	MG/DC	30				
F3206CV20◎			2	0,1	11											
F3206CV25◎			2,5	0,15	7											
F3206CV30◎			3	0,25	6,5											
F3206CV35◎			3,5	0,32	4											
F3206CV40◎			4	0,36	3,5											
F3206CV45◎			4,5	0,41	3											
F3206CV52◎			5,2	0,47	2,2											
F3206CV15◎	3/8"	1/2"	1,5	0,07	23	23		40	30	27	MK (AC/DC)	36				
F3206CV20◎			2	0,1	17	17										
F3206CV25◎			2,5	0,15	12	12										
F3206CV30◎			3	0,25	9	9										
F3206CV35◎			3,5	0,32	7	7										
F3206CV40◎			4	0,36	5,5	5,5										
F3206CV45◎			4,5	0,41	4,5	4,5										
F3206CV52◎			5,2	0,47	3	3										
F3206CV64◎			6,4	0,64	3,5	3,5										

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3206CV25◎ => F3206DV25MG5:

2-way solenoid valve normally open, direct acting poppet type with G connection (ISO 228) 1/2", FPM seals, 2,5 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body
- Brass guide tube
- AISI 304R stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):


- Stainless steel guide tube
- Chemical nickel plating surface treatment
- certified solenoid coils
- Versions for use with fluid temperature at -40 °C
- Manual override

Technical characteristics

Maximum admitted pressure (bar)	50
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80
Mounting position	Indifferent
Weight (g) with solenoid coil MG series	300
Weight (g) with solenoid coil MK series	380



► **F3305 - 3-way solenoid valve brass body, with G connection (ISO 228) - 1/8"**




CODE "V" = FPM seals	G connection (ISO 228) ◎ = Connection	Orifice (mm)		KV (m ³ /h)	Differential pressure (bar)			Power consumption			◎ = Solenoid coil	Temperature range (°C)
		A	Inlet		Min	Max	AC	DC	AC Inrush (VA)	AC Holding (VA)	DC (W)	
N.C. - Normally closed												
F3305CV12◎	1/8"		1,2	1,5	0,04	0	15	15	12	8	6,5	MI 22
F3305CV15◎			1,5	1,5	0,06		10	10				
F3305CV20◎			2	1,7	0,09		6	6				
N.O. - Normally open												
F3305CV15S◎	1/8"		1,5	1,5	0,06	0	10	10	12	8	6,5	MI 22
F3305CV17S◎			1,7	2	0,07		6	6				
U - Universal												
F3305CV15U◎	1/8"	1,5	1,5	0,06	0	6	6	12	8	6,5	MI	22

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3305CV12◎ => F3305AV12MI5:

3-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/8", FPM seals, 1,2 mm inlet orifice, solenoid coil 24 VDC (MI5, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body
- Brass guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):


- Stainless steel guide tube
- Chemical nickel plating surface treatment
- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC
- cULus certified solenoid coils
- Exhaust port with hose tail connection
- Versions for use with fluid temperature at -40 °C
- Manual override

Technical characteristics

Maximum admitted pressure (bar)	50
Maximum fluid viscosity (mm ² /s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Universal

Weight (g) 110

► F3306 - 3-way solenoid valve brass body, with G connection (ISO 228) - 1/8" and 1/4"





CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection		Orifice (mm)		KV (m³/h)	Differential pressure (bar)		Power consumption			◎= Solenoid coil		Temperature range (°C)		
	A	B	Inlet	Exhaust		Min	Max	AC	DC	AC Inrush (VA)	AC Holding (VA)	DC (W)	Series		
N.C. - Normally closed														-10 ... +140	
F3306CV15◎	1/8"	1/4"	1,5	2,4	0,07	0	20	20	20	15	10	MG	30		
F3306CV20◎			2	2,4	0,11		13	13							
F3306CV25◎			2,5	2,4	0,16		10	10							
N.O. - Normally open															
F3306CV25S◎	1/8"	1/4"	2,4	2,5	0,16	0	9	9	20	15	10	MG	30		
F3306CV29S◎			2,9	3	0,20		6,5	6,5							
U - Universal															
F3306CV25UE◎	1/8"	1/4"	2,5	2,4	0,16	0	5	4	20	15	10	MG	30		

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).

Example: F3306CV15◎ => F3306AV15MG5:

3-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/8", FPM seals, 1,5 mm inlet orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Construction characteristics

- Brass body
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):


- Manual override
- Chemical nickel plating surface treatment
- UL certified solenoid coils
- Versions for use with fluid temperature at -40 °C

Technical characteristics

Maximum admitted pressure (bar)	80
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Indifferent
Weight (g)	125



► **F3310 - 3-way solenoid valve stainless steel body, with G connection (ISO 228) - 1/4"**




CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection	Orifice (mm)		KV (m³/h)	Differential pressure (bar)			Power consumption			◎= Solenoid coil	Temperature range (°C)			
		B	Inlet		Min	Max	AC	DC	AC Inrush (VA)	AC Holding (VA)	DC (W)	Series	Size		
N.C. - Normally closed															
F3310CV20◎	1/4"	2	2,4	0,11	0	13	13	20	15	10	MG	30	-10 ... +140		
F3310CV25◎		2,5	2,4	0,16		10	10								
N.O. - Normally open															
F3310CV25SE◎	1/4"	2,4	2,5	0,16	0	9	9	20	15	10	MG	30			
F3310CV29SE◎		2,9	3	0,20		6,5	6,5								
U - Universal															
F3310CV25UE◎	1/4"	2,5	2,4	0,16	0	5	4	20	15	10	MG	30			

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3310CV20◎ => F3310BV20MG5:

3-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/4", FPM seals, 2 mm inlet orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- AISI 303 stainless steel body
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):


- Silver advance ring
- certified solenoid coils
- Versions for use with fluid temperature at -40 °C

Technical characteristics

Maximum admitted pressure (bar)	80
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Indifferent
Weight (g)	360



► F3311 - 3-way solenoid valve stainless steel body, with G connection (ISO 228) - 1/8"






CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection	Orifice (mm)		KV (m³/h)	Differential pressure (bar)		Power consumption			◎= Solenoid coil	Temperature range (°C)
		A	Inlet		Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)		
N.C. - Normally closed											
F3311◎V12◎	1/8"	1,2	1,5	0,04	0	15	15	12	8	6,5	MI
F3311◎V15◎		1,5	1,5	0,06		10	10				
F3311◎V20◎		2	1,7	0,09		6	6				
N.O. - Normally open											
F3311◎V15S◎	1/8"	1,5	1,5	0,06	0	10	10	12	8	6,5	MI
F3311◎V17S◎		1,7	2	0,07		6	6				
U - Universal											
F3311◎V15U◎	1/8"	1,5	1,5	0,06	0	6	6	12	8	6,5	MI
N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).											


Example: F3311◎V20◎ => F3311AV20MI58;

3-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/8", FPM seals, 2 mm inlet orifice, solenoid coil 230 VAC (50-60 Hz) (MI58, size 22 for more information, please refer to the section "Solenoid coils - Series F300").


Pneumatic symbol



Diagram



N.C.



N.O.

Construction characteristics

- AISI 303 stainless steel body
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):


- Silver advance ring
- certified solenoid coils
- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC
- Exhaust port with hose tail connection
- Versions for use with fluid temperature at -40 °C

Technical characteristics

Maximum admitted pressure (bar)	50
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Indifferent
Weight (g)	150



► **F332 - 3-way solenoid valve stainless steel or anodised aluminium body, with G connection (ISO 228) - 1/4"**




CODE "V" = FPM seals	G connection (ISO 228) Ⓐ = Connection	Orifice (mm)		KV (m³/h)	Differential pressure (bar)		Power consumption			Ⓑ = Solenoid coil	Temperature range (°C)
		Inlet	Exhaust		Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)		
Anodised aluminium body											
U - Universal											
F3320BV75B	1/4"	7,5	7,5	0,64	0	5	5	40	30	27	MK 36
N.C. - Normally closed											
F3321BV75B	1/4"	7,5	7,5	0,64	0	9	9	40	30	27	MK 36
N.O. - Normally open											
F3322BV75B	1/4"	7,5	7,5	0,64	0	9	9	40	30	27	MK 36
Stainless steel body											
U - Universal											
F3323BV75B	1/4"	7,5	7,5	0,64	0	5	5	40	30	27	MK 36
N.C. - Normally closed											
F3324BV75B	1/4"	7,5	7,5	0,64	0	9	9	40	30	27	MK 36
N.O. - Normally open											
F3325BV75B	1/4"	7,5	7,5	0,64	0	9	9	40	30	27	MK 36

Example: F3321BV75B => F3321BV75MK5:


3-way solenoid valve normally closed, direct acting poppet type aluminium body with G connection (ISO 228) 1/4", FPM seals, 7,5 mm inlet orifice, solenoid coil 24 VDC (MK5, size 36 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Construction characteristics	Technical characteristics
- AISI 303 stainless steel or anodised aluminium body	Maximum admitted pressure (bar) 50
- AISI 303 stainless steel guide tube	Maximum fluid viscosity (mm²/s) 25cSt
- AISI 430FR stainless steel mobile and fixed core	Ambient temperature: with class H solenoid coil (°C) -10 ... +80
- AISI 302 stainless steel springs	Mounting position Indifferent
- FPM sealing assemblies	Weight (g) 430

► F3371 - 3-way solenoid valve stainless steel body, with G connection (ISO 228) - 1/8"






CODE "V" = FPM seals	G connection (ISO 228) ①= Connection	Orifice (mm)		KV (m³/h)	Differential pressure (bar)		Power consumption			②= Solenoid coil	Temperature range (°C)
		Inlet	Exhaust		Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)		
N.C. - Normally closed											
F3371CV12③	1/8"	1,2	1,5	0,04	0	15	15	12	8	6,5	MI
F3371CV15③		1,5	1,5	0,06		10	10				
F3371CV20③		2	1,5	0,09		6	6				
N.O. - Normally open											
F3371CV15SB	1/8"	1,5	1,5	0,06	0	10	10	12	8	6,5	MI
U - Universal											
F3371CV15UB	1/8"	1,5	1,5	0,06	0	6	6	12	8	6,5	MI
N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).											


Example: F3371CV12③ => F3371AV12M158:

3-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/8", FPM seals, 1,2 mm inlet orifice, solenoid coil 230 VAC (50-60 Hz) (M158, size 22 for more information, please refer to the section "Solenoid coils - Series F300").


Pneumatic symbol



Diagram



N.C.



N.O.

Construction characteristics


- AISI 316 stainless steel body
 - AISI 316 stainless steel guide tube
 - AISI 430FR stainless steel mobile and fixed core
 - Silver advance ring
 - AISI 316 stainless steel springs
 - FPM sealing assemblies
- OPTIONS (on request):**
- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC
 - Exhaust port with hose tail connection
 - certified solenoid coils
 - Versions for use with fluid temperature at -40 °C

Technical characteristics

Maximum admitted pressure (bar)	50
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Indifferent
Weight (g)	150



► **F3370 - 3-way solenoid valve stainless steel body, with G connection (ISO 228) - 1/4"**




CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection	Orifice (mm)		KV (m³/h)	Differential pressure (bar)			Power consumption			◎= Solenoid coil	Temperature range (°C)	
		B	From 1 to 2		Min	Max	AC	DC	AC Inrush (VA)	AC Holding (VA)	DC (W)		
N.C. - Normally closed													
F3370CV15◎	1/4"		1,5	2,4	0,07	0	16	16	20	15	10	MG	30
F3370CV20◎			2	2,4	0,11		13	13					
F3370CV25◎			2,5	2,4	0,16		10	10					
N.O. - Normally open													
F3370CV24S◎	1/4"		2,4	2,5	0,16	0	9	9	20	15	10	MG	30
U - Universal													
F3370CV25U◎	1/4"		2,5	2,4	0,16	0	5	4	20	15	10	MG	30

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).

Example: F3370CV15◎ => F3370BV15MG5:


3-way solenoid valve normally closed, direct acting poppet type with G connection (ISO 228) 1/4", FPM seals, 1,5 mm orifice, from 1 to 2, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol




Diagram

N.C.



N.O.



Construction characteristics

- AISI 316 stainless steel body
- AISI 316 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- Silver advance ring
- AISI 316 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):



- For use with oxygen
- certified solenoid coils
- Versions for use with fluid temperature at -40 °C

Technical characteristics

Maximum admitted pressure (bar)	80
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Indifferent
Weight (g)	360



► FX3370 - 3-way solenoid valve N.C. stainless steel body, with G connection (ISO 228)
with certified housing: Ex d IIC T6 or T5 or T4 Gb - 1/4"




CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection	Orifice (mm)		KV (m³/h)	Differential pressure (bar)		Power consumption		◎= Solenoid coil	Temperature range (°C)
		B	From 1 to 2		Min	Max	AC Holding (VA)	DC (W)		
			From 2 to 3		AC	DC				
FX3370CV15◎	1/4"	1,5	2,4	0,07	0	16	16	12	8	A6B= 24 Volt (AC 50-60 Hz) A6E= 220/230 Volt (AC 50-60 Hz) A60= 12 Volt (DC) A61= 24 Volt (DC)
FX3370CV20◎			2,4	0,11		13	13			
FX3370CV25◎		2,5	2,4	0,16		10	10			

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: FX3370CV15◎ => FX3370BV15A60:

3-way solenoid valve normally closed, direct acting poppet type with certified housing: Ex d IIC T6 or T5 or T4 Gb, with G connection (ISO 228) 1/4", FPM seals, 1,5 mm orifice, from 1 to 2, solenoid coil 12 VDC (A60).


Pneumatic symbol



Diagram



Construction characteristics	Technical characteristics
- AISI 316 stainless steel body	Maximum admitted pressure (bar) 80
- AISI 316 stainless steel guide tube	Maximum fluid viscosity (mm²/s) 25cSt
- AISI 430FR stainless steel mobile and fixed core	Ambient temperature (°C) -40 ... +60
- AISI 316 stainless steel springs	Mounting position Vertical with solenoid coil upwards
- Red light alloy housing	
- 1/2" NPT electrical connection (M20x1,5 on request)	
- FPM sealing assemblies	Weight (g) 650



CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection						Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			◎= Solenoid coil	Temperature range (°C)				
	B	C	D	E	F	G			Min	Max		AC Inrush (VA)	AC Holding (VA)	DC (W)					
										AC	DC								
F3107◎V10◎	1/4"		/				10	1,5	0,15	15	15	12	8	6,5	MI	22	-10 ... +140		
F3107◎V10◎	/	3/8"		/			10	1,7		15	15								
F3107◎V12◎	/	3/8"		/			12	2,2		15	15								
F3107◎V12◎	/	1/2"		/			12	2,5		15	15								
F3107◎V18◎	/		3/4"		/		18	5,5		13	13								
F3107◎V25◎	/		1"		/		25	10,2		10	10								
F3107◎V30◎	/		1" 1/4				30	15		10	10								


G connection	1/4" Ø10	3/8" Ø10	3/8" Ø12	1/2" Ø12	3/4"	1"	1" 1/4 Ø30
a	49	49	59	59	79	96	119
b	65	65	70	70	76	85	92
c	11	11	14	14	18	20	25
d	32	32	45	45	55	72	85
e			16				
f			22				
Weight (g)	230	240	420	390	650	1050	1700

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3107◎V25◎ => F3107FV25MI58:

2-way solenoid valve normally closed, servo-assisted diaphragm with G connection (ISO 228) 1", FPM seals, 25 mm orifice, solenoid coil 230 VAC (50-60 Hz) (MI58, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body and cover
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):

- Manual override
- Chemical nickel plating surface treatment
- Version with slowed commutation
- Version for vacuum (air/gas)
- For use with oxygen
- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC
- cULus certified solenoid coils


Technical characteristics

Maximum admitted pressure (bar)	25
Minimum differential pressure (bar)	0,15
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55

Mounting position

Preferably with solenoid coil upwards

► F3107 - 2-way solenoid valve N.C. brass body and cover, with G connection (ISO 228) - 1" 1/4 ... 3"



CODE "V" = FPM seals "B" = NBR seals	G connection (ISO 228) ◎ = Connection					Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			◎ = Solenoid coil	Temperature range (°C)		
	G	H	I	M	R			Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)				
F3107CV37◎	1" 1/4	/				37	18	0,15	10	10	20	10	MG	30	-10 ... +140	
F3107CV37◎	/	1" 1/2	/			37	21		10	10						
F3107CV50◎	/	2"	/			50	36		10	10						
F3107CB75◎	/	2" 1/2	/			75	75	0,3	5	5	20	15	10	MG	30	-10 ... +90
F3107CB75◎	/	3"				75	84		5	5						


G connection	1" 1/4	1" 1/2	2"	2" 1/2	3"
a	142	142	158	226	226
b	105	105	115	134	134
c	28	28	35	51	51
d	102	102	119	169	169
e			21		
f			30		
Weight (g)	3000	2850	4300	1170	9900

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3107CV37◎ => F3107GV37MG5:

2-way solenoid valve normally closed, servo-assisted diaphragm with G connection (ISO 228) 1" 1/4, FPM seals, 37 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body and cover
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies (NBR only for "M" and "R" versions)

OPTIONS (on request):

- Manual override
- Chemical nickel plating
- Version for vacuum (air/gas)
- cULus certified solenoid coils

Technical characteristics


Maximum admitted pressure (bar)	20
Minimum differential pressure (bar)	0,15 ... 3
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55

Mounting position

Preferably with solenoid coil upwards



► **FX3107 - 2-way solenoid valve N.C. brass body and cover, with G connection (ISO 228)**
with certified housing: Ex d IIC T6 or T5 or T4 Gb - 1/4" ... 3"



CODE "V" = FPM seals "B" = NBR seals	G connection (ISO 228) ◎ = Connection									Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption		◎ = Solenoid coil	Temperature range (°C)
	B	C	D	E	F	G	H	I	M			Min	Max	AC	DC		
FX3107CV10◎	1/4"					/				10	1,5						
FX3107CV10◎	/	3/8"				/				10	1,7						
FX3107CV12◎	/	3/8"				/				12	2,2						
FX3107CV12◎	/	1/2"				/				12	2,5						
FX3107CV18◎	/	3/4"				/				18	5,5						
FX3107CV25◎	/	1"				/				25	10,2						
FX3107CV30◎	/	1" 1/4				/				30	15						
FX3107CV37◎	/	1" 1/4				/				37	18						
FX3107CV37◎	/	1" 1/2				/				37	21						
FX3107CV50◎	/				2"		/			50	36						
FX3107CB75◎	/				2" 1/2		/			75	75						
FX3107CB75◎					3"					75	84	0,3		5	5		


G connection	1/4" Ø10	3/8" Ø10	3/8" Ø12	1/2" Ø12	3/4"	1"	1"1/4 Ø30	1"1/4	1"1/2	2"	2"1/2	3"
a	49	49		59	59	79	96	119	142	142	158	226
b	90	90	95	95	101	110	118	110	110	110	119	138
c	11	11	14	14	18	20	25	28	28	35	51	51
d	32	32	45	45	54	72	85	102	102	119	169	169
e	71	71	76	76	82	91	99	91	91	100	119	119
Weight (g)	720	720	920	920	1100	1500	2270	3330	3120	4720	10400	10000

N.B. The solenoid valve is suited for intercepting only fluids that are NOT potentially explosive.


Example: FX3107CV10◎ => FX3107BV10A60:

2-way solenoid valve normally closed, servo-assisted diaphragm with certified housing: Ex d IIC T6 or T5 or T4 Gb, with G connection (ISO 228) 1/4", FPM seals, 10 mm orifice, solenoid coil 12 VDC (A60).

Pneumatic symbol




Diagram



Construction characteristics		Technical characteristics	
- Brass body and cover		Maximum admitted pressure (bar)	25
- Red light alloy housing		Minimum differential pressure (bar)	0,15 ... 0,3
- 1/2" NPT electrical connection (M20x1,5 on request)		Maximum fluid viscosity (mm²/s)	25cSt
- FPM sealing assemblies (NBR only for "M" and "R" versions)		Ambient temperature (°C)	-40 ... +60
OPTIONS (on request):		Mounting position	Vertical with solenoid coil upwards
- Chemical nickel plating surface treatment			
- Version with slowed commutation			

► F3177 - 2-way solenoid valve N.C. stainless steel body and cover, with G connection (ISO 228) - 3/8" ... 1"



CODE "V"= FPM seals	G connection (ISO 228) ∅= Connection				Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			∅= Solenoid coil	Temperature range (°C)	
	C	D	E	F			Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)			
F3177CV12	3/8"	/	/		12	2,2	0,15	15	15	12	6,5	MI	22	-10 ... +140
F3177CV12	/	1/2"	/		12	2,5		15	15					
F3177CV18	/	3/4"	/		18	5,5		13	13					
F3177CV25	/	1"			25	10,2		10	10					


G connection	3/8"	1/2"	3/4"	1"
a	59	59	79	96
b	70	70	76	85
c	11	13	18	20
d	45	45	55	72
e			16	
f			22	
Weight (g)	300	320	550	950

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3177CV12 => F3177CV12MI58:

2-way solenoid valve normally closed, servo-assisted diaphragm with G connection (ISO 228) 3/8", FPM seals, 12 mm orifice, solenoid coil 230 VAC (50-60 Hz) (MI58, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- AISI 316 stainless steel body and cover
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):

- Manual override
- Seals for use with foodstuff fluids
- Version with slowed commutation
- Silver advance ring
- For use with oxygen
- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC
- cULus and IECEx certified solenoid coils

Technical characteristics


Maximum admitted pressure (bar)	25
Minimum differential pressure (bar)	0,15
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55

Mounting position

Preferably with solenoid coil upwards



► **FX3177 - 2-way solenoid valve N.C. stainless steel body and cover, with G connection (ISO 228)
with certified housing: Ex d IIC T6 or T5 or T4 Gb - 3/8" ... 1"**



CODE "V" = FPM seals	G connection (ISO 228) ⊖= Connection				Orifice (mm)	KV (m³/h)	Differential pressure (bar)				⊖= Solenoid coil	Temperature range (°C)			
	C	D	E	F			Min	Max		AC Holding (VA)	DC (W)				
								AC	DC						
FX3177CV121	3/8"		/		12	2,2		15	15						
FX3177CV120	/	1/2"	/		12	2,5		15	15						
FX3177CV181	/		3/4"	/	18	5,5	0,15	13	13	12	8	A6B = 24 Volt (AC 50-60 Hz) A6E = 220/230 Volt (AC 50-60 Hz) A60 = 12 Volt (DC) A61 = 24 Volt (DC)			
FX3177CV251		/		1"	25	10,2		10	10			-10 ... +80			


G connection	3/8" Ø12	1/2" Ø12	3/4"	1"
a	59	59	79	96
b	95	95	101	110
c	14	14	18	20
d	45	45	54	72
e	76	76	82	91
Weight (g)	1120	1110	1100	1500

N.B. The solenoid valve is suited for intercepting only fluids that are NOT potentially explosive.


Example: FX3177CV120 => FX3177CV12A60:

2-way solenoid valve normally closed, servo-assisted diaphragm with certified housing: Ex d IIC T6 or T5 or T4 Gb, with G connection (ISO 228) 3/8", FPM seals, 12 mm orifice, solenoid coil 12 VDC (A60).

Pneumatic symbol



Diagram



Construction characteristics

- AISI 316 stainless steel body and cover
- Red light alloy housing
- 1/2" NPT electrical connection (M20x1,5 on request)
- FPM sealing assemblies


OPTIONS (on request):

- Version with slowed commutation

Technical characteristics

Maximum admitted pressure (bar)	25
Minimum differential pressure (bar)	0,15
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature (°C)	-40 ... +60
Mounting position	Vertical with solenoid coil upwards

► F3277 - 2-way solenoid valve N.O. stainless steel body and cover, with G connection (ISO 228) - 3/8" ... 1"




CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection				Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			◎= Solenoid coil	Temperature range (°C)		
	C	D	E	F			Min	Max	AC	DC	AC Inrush (VA)	AC Holding (VA)	DC (W)	Series	Size
F3277CV12◎	3/8"	/	/	/	12	2,2	0,15	15	15	12	8	6,5	MI	22	-10 ... +140
F3277CV12◎	/	1/2"	/	/	12	2,5		15	15						
F3277CV18◎	/	3/4"	/	/	18	5,5		13	13						
F3277CV25◎	/	1"	1"	1"	25	10,2		10	10						
G connection	3/8"	1/2"	3/4"	1"											
a	59	59	79	96											
b	73	73	76	85											
c	14	14	18	20											
d	45	45	55	72											
e	16														
f	22														
Weight (g)	300	320	550	950											

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3277CV12◎ => F3277CV12M158:

2-way solenoid valve normally open, servo-assisted diaphragm, with G connection (ISO 228) 3/8", FPM seals, 12 mm orifice, solenoid coil 230 VAC (50-60 Hz) (M158, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- AISI 316 stainless steel body and cover
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies

OPTIONS (on request):

- Seals for use with foodstuff fluids
- Version with slowed commutation
- Silver advance ring
- For use with oxygen
- XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC
- FM us certified solenoid coils

Technical characteristics


Maximum admitted pressure (bar)	25
Minimum differential pressure (bar)	0,15
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55

Mounting position

Preferably with solenoid coil upwards



► **F3207 - 2-way solenoid valve N.O. brass body and cover, with G connection (ISO 228) - 1/4" ... 1" 1/4**



CODE "V" = FPM seals	G connection (ISO 228) ⊖= Connection						Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			⊖= Solenoid coil	Temperature range (°C)	
	B	C	D	E	F	G			Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)			
F3207CV10B	1/4"		/				10	1,5	0,15	15	15	12	6,5	MI	22	-10 ... +140
F3207CV10B	/	3/8"		/			10	1,7		15	15					
F3207CV12B	/	3/8"		/			12	2,2		15	15					
F3207CV12B	/	1/2"		/			12	2,5		15	15					
F3207CV18B	/	3/4"		/			18	5,5		13	13					
F3207CV25B	/		1"	/			25	10,2		10	10					
F3207CV30B	/		1" 1/4				30	15		10	10					


G connection	1/4" Ø10	3/8" Ø10	3/8" Ø12	1/2" Ø12	3/4"	1"	1" 1/4 Ø30
a	49	49	59	59	79	96	119
b	65	65	73	73	76	85	96
c	11	11	14	14	18	20	25
d	32	32	45	45	55	72	85
e				16			
f				22			
Weight (g)	230	240	420	390	650	1050	1700

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3207CV10B => F3207CV10MI58:

2-way solenoid valve normally open, servo-assisted diaphragm, with G connection (ISO 228) 1/4", FPM seals, 10 mm orifice, solenoid coil 230 VAC (50-60 Hz) (MI58, size 22 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol




Diagram



Construction characteristics	Technical characteristics
- Brass body and cover - AISI 303 stainless steel guide tube - AISI 430FR stainless steel mobile and fixed core - AISI 302 stainless steel springs - FPM sealing assemblies	Maximum admitted pressure (bar) 25
OPTIONS (on request): - Manual override - Chemical nickel plating surface treatment - XME solenoid coil for potentially explosive environments to ATEX standards - Ex mb IIC - cULus certified solenoid coils	Minimum differential pressure (bar) 0,15
	Maximum fluid viscosity (mm²/s) 25cSt
	Ambient temperature: with class F solenoid coil (°C) -10 ... +55
	Mounting position Preferably with solenoid coil upwards

► F3207 - 2-way solenoid valve N.O. brass body and cover, with G connection (ISO 228) - 1" 1/4 ... 3"



CODE "V" = FPM seals "B" = NBR seals	G connection (ISO 228) ∅= Connection					Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			∅= Solenoid coil	Temperature range (°C)		
	G	H	I	M	R			Min	Max	AC	DC	AC Inrush (VA)	AC Holding (VA)	DC (W)		
F3207CV37(B)	1" 1/4	/				37	18	0,15	10	10	10	20	15	MG	30	-10 ... +140
F3207CV37(B)	/	1" 1/2	/			37	21		10	10						
F3207CV50(B)	/	2"	/			50	36		10	10						
F3207CB75(B)	/	2" 1/2	/			75	75	0,3	5	5	10	20	15	MG	30	-10 ... +90
F3207CB75(B)	/	3"				75	84		5	5						


G connection	1" 1/4	1" 1/2	2"	2" 1/2	3"
a	142	142	158	226	226
b	105	105	115	134	134
c	28	28	35	51	51
d	102	102	119	169	169
e			21		
f			30		
Weight (g)	3000	2850	4300	1170	9900

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3107CV37(B) => F3107GV37MG5:

2-way solenoid valve normally closed, servo-assisted diaphragm with G connection (ISO 228) 1" 1/4, FPM seals, 37 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body and cover
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies (NBR only for "M" and "R" versions)

OPTIONS (on request):

- Manual override
- Chemical nickel plating
- Version for vacuum (air/gas)
- cULus certified solenoid coils

Technical characteristics


Maximum admitted pressure (bar)	20
Minimum differential pressure (bar)	0,15 ... 3
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55

Mounting position

Preferably with solenoid coil upwards



► **F3108 - 2-way solenoid valve N.C. brass body and cover, with G connection (ISO 228) - 3/8" ... 1"**



The data in
brackets refer
to the MK Series coil

CODE "V" = FPM seals	G connection (ISO 228) ⊖= Connection				Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			⊖= Solenoid coil	Temperature range (°C)	
	C	D	E	F			Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)			
AC	DC													
F3108CV12B	3/8"	/			12	2	0	10	/	20	15	/	MG/AC	30
F3108CV12B	/	1/2"	/		12	2,2		10	/					
F3108CV12B	3/8"	/			12	2		12	10	40	30	27		
F3108CV12B	/	1/2"	/		12	2,2		12	10					
F3108CV18B	/	3/4"	/		18	4,5		9	/	40	30	/		MK (AC/DC)
F3108CV25B	/	1"	/		25	8,5		7	/					
F3108CV18CB	/	3/4"	/		18	4,5		/	9			27		
F3108CV25CB	/	1"			25	8,5		/	8			MK/DC		


G connection	3/8"	1/2"	3/4"	1"
a	59	59	79	96
b	83	83	90	101
c	14	14	18	20
d	45	45	55	72
Weight (g)	MG	520	490	/
	MK	600	570	810
				1220

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3108CV12B => F3108CV12MG5:

2-way solenoid valve normally closed, with assisted-lift diaphragm with G connection (ISO 228) 3/8", FPM seals, 12 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body and cover
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- FPM sealing assemblies


OPTIONS (on request):

- Chemical nickel plating
- certified solenoid coils

Technical characteristics

Maximum admitted pressure (bar)	25
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80
Mounting position	Preferably with solenoid coil upwards

► F3168 - 2-way solenoid valve N.C. brass body and cover, with G connection (ISO 228) - 3/8" ... 1" 1/2



CODE "V" = FPM seals	G connection (ISO 228) ◎ = Connection						Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption		◎ = Solenoid coil		Temperature range (°C)			
	C	D	E	F	G	H			Min	Max		(W)		Series	Size			
										AC	DC							
F3168CV11◎	3/8"			/			11	1,2	0	14	5	10	MG	30	-10 ... +140			
										/	14	27	MK	36				
F3168CV16◎	/	1/2"			/		16	2,4		14	2,5	10	MG	30				
										/	14	27	MK	36				
F3168CV16◎	/	3/4"			/		16	2,4		14	2,5	10	MG	30				
										/	14	27	MK	36				
F3168CV20H◎	/	3/4"			/		20	7,2		16	5	10	MG	30				
										/	16	27	MK	36				
F3168CV25◎			1"		/		25	7,2		8	/	10	MG	30				
										14	1,5	14	MK	36				
F3168CV25H◎			1"		/		25	8,4		/	6	27	MK	36				
										16	5	10	MG	30				
F3168CV35◎				1" 1/4		/	35	16,2		/	16	27	MK	36				
										16	/	10	MG	30				
F3168CV40◎					1" 1/2		40	16,8		/	6	14	MK	36				
										/	16	27	MK	36				


G connection	3/8"	1/2"	3/4"	3/4" (H)	1"	1" (H)	1" 1/4	1" 1/2
a	50	50	50	65	65	65	94	94
b	89	100	100	103	112	110	130	130
c	56	70	70	104	104	104	128	128

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3168CV11◎ => F3168CV11MG5:

2-way solenoid valve normally closed, with assisted-lift diaphragm with G connection (ISO 228) 3/8", FPM seals, 11 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol




Diagram



Construction characteristics	Technical characteristics
- Brass body and cover	Maximum admitted pressure (bar)
- AISI 303 stainless steel guide tube	16
- AISI 430FR stainless steel mobile and fixed core	Maximum fluid viscosity (mm²/s)
- AISI 302 stainless steel springs	25cSt
- FPM sealing assemblies (NBR on request)	Ambient temperature: with class F solenoid coil (°C)
OPTIONS (on request):	-10 ... +55
- NPT connections	Ambient temperature: with class H solenoid coil (°C)
- ATEX Ex d explosion protection solenoid coil	-10 ... +80
- For use with oxygen	
- FM us certified solenoid coils	Mounting position
	Preferably with solenoid coil upwards



► **F3178 - 2-way solenoid valve N.C. stainless steel body and cover, with G connection (ISO 228) - 3/8" ... 1" 1/2**



CODE "V" = FPM seals	G connection (ISO 228) ◎ = Connection						Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption		◎ = Solenoid coil	Temperature range (°C)			
	C	D	E	F	G	H			Min	Max	(W)	Series	Size				
									AC	DC							
F3178CV15◎	3/8"	/					15	2,4	0	14	6	10	MG	30			
		/	1/2"	/			16	3		/	14	27	MK	36			
F3178CV16◎		/	1/2"	/			16	3		14	6	10	MG	30			
		/	1/2"	/			16	3		/	14	27	MK	36			
F3178CV20◎		/	3/4"	/			20	3,6		14	6	10	MG	30			
		/	3/4"	/			20	3,6		/	14	27	MK	36			
F3178CV25◎		/	1"	/			25	8,4		14	3	10	MG	30			
		/	1"	/			25	8,4		/	8	14	MK	36			
F3178CV35◎		/	1" 1/4	/			35	18		/	14	27	MK	36			
		/	1" 1/4	/			35	18		8	/	10	MG	30			
F3178CV40◎		/	1" 1/2	/			40	19,2		14	2	14	MK	36			
		/	1" 1/2	/			40	19,2		/	7	27	MK	36			


G connection	3/8"	1/2"	3/4"	1"	1" 1/4	1" 1/2
a	52	52	58	65	94	94
b	92	92	100	109	126	126
c	68	68	75	90	128	128

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3178CV15◎ => F3178CV15MG5:

2-way solenoid valve normally closed, with assisted-lift diaphragm with G connection (ISO 228) 3/8", FPM seals, 15 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- AISI 316 stainless steel body and cover
- AISI 316 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- Silver advance ring
- FPM sealing assemblies (NBR on request)

OPTIONS (on request):

- NPT connections
- ATEX Ex d explosion protection solenoid coil
- For use with oxygen
- cULus certified solenoid coils

Technical characteristics


Maximum admitted pressure (bar)	16
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80

Mounting position

Preferably with solenoid coil upwards



► FX3168 - 2-way solenoid valve N.C. brass body, with G connection (ISO 228)
with certified housing: Ex d IIC T6 or T5 or T4 Gb - 3/8" ... 1"




CODE "V"= FPM seals	G connection (ISO 228) ①= Connection				Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption (W)	②= Solenoid coil	Temperature range (°C)					
	Min		Max				Min									
	C	D	E	F			AC	DC								
FX3168CV11B	3/8"	/	/		11	1,2	0	5	5	8	A6B= 24 Volt (AC 50-60 Hz) A6E= 220/230 Volt (AC 50-60 Hz) A60= 12 Volt (DC) A61= 24 Volt (DC)					
FX3168CV16B	/	1/2"	/		16	2,4		5	5							
FX3168CV16B	/	3/4"	/		16	2,4		5	5							
FX3168CV20HB	/	3/4"	/		20	7,2		5	5							
FX3168CV25HB	/		1"		25	8,4		5	5							

G connection	3/8"	1/2"	3/4"	3/4" (H)	1" (H)
a	50	50	50	65	65
b	95	106	106	109	116
c	56	70	70	104	104


Example: FX3168CV11B => FX3168CV11A60:

2-way solenoid valve normally closed, with assisted-lift diaphragm with certified housing: Ex d IIC T6 or T5 or T4 Gb, with G connection (ISO 228) 3/8", FPM seals, 11 mm orifice, solenoid coil 12 VDC (A60).

Pneumatic symbol



Diagram



Construction characteristics


- Brass body
- Red light alloy housing
- 1/2" NPT electrical connection (M20x1,5 on request)
- FPM sealing assemblies

Technical characteristics

Maximum admitted pressure (bar)	16
Minimum differential pressure (bar)	0
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature (°C)	-40 ... +60
Mounting position	Vertical with solenoid coil upwards



► **FX3178 - 2-way solenoid valve N.C. stainless steel body, with G connection (ISO 228)
with certified housing: Ex d IIC T6 or T5 or T4 Gb - 3/8" ... 1"**




CODE "V"= FPM seals	G connection (ISO 228) ⊖= Connection				Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption (W)	⊖= Solenoid coil	Temperature range (°C)
	C	D	E	F			Min	Max	AC	DC	
FX3178CV15⊖	3/8"	/			15	2,4	0	6	6	8	A6B= 24 Volt (AC 50-60 Hz) A6E= 220/230 Volt (AC 50-60 Hz) A60= 12 Volt (DC) A61= 24 Volt (DC)
FX3178CV16⊖	/	1/2"	/		16	3		6	6		
FX3178CV20⊖	/	3/4"	/		20	3,6		6	6		
FX3178CV25⊖		/	1"		25	8,4		3	3		


G connection	3/8"	1/2"	3/4"	1"
a	52	52	58	65
b	98	98	106	115
c	68	68	75	90

Example: FX3178⊖V15⊖ => FX3178CV15A60:
2-way solenoid valve normally closed, with assisted-lift diaphragm with certified housing: Ex d IIC T6 or T5 or T4 Gb, with G connection (ISO 228) 3/8", FPM seals, 15 mm orifice, solenoid coil 12 VDC (A60).

Pneumatic symbol



Diagram



Construction characteristics

- AISI 316 stainless steel body
- Red light alloy housing
- 1/2" NPT electrical connection (M20x1,5 on request)
- FPM sealing assemblies

OPTIONS (on request):


- Solenoid coil with stainless steel housing

Technical characteristics

Maximum admitted pressure (bar)	16
Minimum differential pressure (bar)	0
Maximum fluid viscosity (mm²/s)	25cSt
Ambient temperature (°C)	-40 ... +60
Mounting position	Vertical with solenoid coil upwards



► F3119 - 2-way solenoid valve N.C. brass body and cover, with G connection (ISO 228) - 1/4" ... 1/2"




CODE "V" = FPM seals	G connection (ISO 228) ◎= Connection			Orifice (mm)	KV (m³/h)	Differential pressure (bar)			Power consumption			◎= Solenoid coil	Temperature range (°C)		
	B	C	D			Min	Max	AC	DC	AC Inrush (VA)	AC Holding (VA)	DC (W)	Series	Size	
F3119◎V52◎	1/4"	/	/	5,2	0,47	1,5	50	50	50	20	15	10	MG	30	-10 ... +140
F3119◎V12◎	/	3/8"	/	12	2	1	30	30	30	40	30	27	MK	36	
F3119◎V12◎	/	1/2"	1/2"	12	2,2	1	30	30	30	40	30	27	MK	36	
F3119◎V12/1◎	/	3/8"	/	12	2	1	50	50	50	40	30	27	MK	36	
F3119◎V12/1◎	/	1/2"	12	2,2	1	50	50	50	50	40	30	27	MK	36	

N.B. For use with steam maximum admitted pressure PS is 2,5 bar (relative pressure).


Example: F3119◎V52◎ => F3119BV52MG5:

2-way solenoid valve normally closed, servo-assisted piston with G connection (ISO 228) 1/4", main seals in PTFE other in FPM, 5,2 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body and cover
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- Brass piston
- PTFE piston seal
- Sealing assemblies mainly PTFE, others FPM

OPTIONS (on request):


- Chemical nickel plating
- UL certified solenoid coils

Technical characteristics

Maximum admitted pressure (bar)	60
Maximum fluid viscosity (mm²/s)	25cSt
Minimum differential pressure (bar)	1
Maximum admitted leakage (NL/h)	<0,2
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80
Mounting position	Preferably with solenoid coil upwards
Weight (g) with solenoid coil MG series	630
Weight (g) with solenoid coil MK series	710




► **F3119W - 2-way solenoid valve N.C. brass body and cover, with G connection (ISO 228) - 3/8" and 1/2"**




CODE "W" = PTFE seals	G connection (ISO 228) ◎= Connection		Orifice (mm)	KV (m³/h)	Differential pressure (bar)			Power consumption			◎= Solenoid coil	Temperature range (°C)			
	C	D			Min	Max		AC Inrush (VA)	AC Holding (VA)	DC (W)	Series	Size			
						AC	DC								
F3119CW12/1◎	3/8"	/	12	2	2,5	10	10	20	15	10	MG	30	-10 ... +180		
F3119CW12/1◎	/	1/2"	12	2,2	2,5	10	10								

Example: F3119CW12/1◎ => F3119CW12/1MG5:
2-way solenoid valve normally closed, servo-assisted piston for use with steam with G connection (ISO 228) 3/8", PTFE seals, 12 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram




Construction characteristics

- Brass body and cover
 - AISI 303 stainless steel guide tube
 - AISI 430FR stainless steel mobile and fixed core
 - AISI 302 stainless steel springs
 - AISI 303 stainless steel piston
 - PTFE piston seal
 - PTFE sealing assemblies
- OPTIONS (on request):**
- Chemical nickel plating surface treatment
 - certified solenoid coils

Technical characteristics

Minimum differential pressure (bar)	2,5
Maximum admitted leakage (NL/h)	<0,2
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Preferably with solenoid coil upwards
Weight (g)	630


▶ F3123 - 2-way solenoid valve N.C. brass body and cover, with G connection (ISO 228) - 3/8"




CODE "W"= PTFE seals	G connection (ISO 228) ◎= Connection C	Orifice (mm)	KV (m³/h)	Differential pressure (bar)		Power consumption			◎= Solenoid coil		Temperature range (°C)
				Min	Max	AC Inrush (VA)	AC Holding (VA)	DC (W)	Series	Size	
F3123CW07◎	3/8"	7	14	0,7	100 80 150 150	20	15	10	MG	30	-10 ... +95

Example: F3123◎W07◎ => F3123CW07MG5:
2-way solenoid valve normally closed, servo-assisted piston with G connection (ISO 228) 3/8", main seals in PTFE other in FPM, 7 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body and cover
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- AISI 303 stainless steel piston
- Sealing assemblies mainly PTFE, others FPM

OPTIONS (on request):


- Chemical nickel plating
- cULus certified solenoid coils

Technical characteristics

Maximum admitted pressure (bar)	200
Maximum fluid viscosity (mm²/s)	12cSt
Minimum differential pressure (bar)	0,7
Maximum admitted leakage (NL/h)	<0,2
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Ambient temperature: with class H solenoid coil (°C)	-10 ... +80
Mounting position	Preferably with solenoid coil upwards




► **F3124 - 2-way solenoid valve N.C. brass body and cover, with G connection (ISO 228) - 1/2"**




CODE "W" = PTFE seals	G connection (ISO 228) ◎= Connection D	Orifice (mm)	KV (m³/h)	Differential pressure (bar)			Power consumption			◎= Solenoid coil Series	Size	Temperature range (°C)			
				Min	Max		AC Inrush (VA)	AC Holding (VA)	DC (W)						
					AC	DC									
F3124◎W12◎	1/2"	12	60	3	100	100	20	15	10	MG	30	-10 ... +95			

Example: F3124◎W12◎ => F3124DW12MG5:
2-way solenoid valve normally closed, servo-assisted piston with G connection (ISO 228) 1/2", main seals in PTFE other in FPM, 12 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body and cover
- AISI 303 stainless steel guide tube
- AISI 430FR stainless steel mobile and fixed core
- AISI 302 stainless steel springs
- PBT piston
- Sealing assemblies mainly PTFE, others FPM


OPTIONS (on request):

- Chemical nickel plating
- cULus certified solenoid coils

Technical characteristics

Maximum admitted pressure (bar)	150
Maximum fluid viscosity (mm²/s)	12cSt
Minimum differential pressure (bar)	3
Maximum admitted leakage (NL/h)	<0,2
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Preferably with solenoid coil upwards

► F3224 - 2-way solenoid valve N.O. brass body and cover, with G connection (ISO 228) - 1/2"




CODE "W"= PTFE seals	G connection (ISO 228) ①= Connection	Orifice (mm)	KV (m³/h)	Differential pressure (bar)			Power consumption			②= Solenoid coil		Temperature range (°C)			
	D			Min	Max		AC Inrush (VA)	AC Holding (VA)	DC (W)	Series	Size				
					AC	DC									
F3224①W12②	1/2"	12	60	3	50	50	20	15	10	MG	30	-10 ... +95			


Example: F3224①W12② => F3224DW12MG5:

2-way solenoid valve normally open, servo-assisted piston with G connection (ISO 228) 1/2", main seals in PTFE other in FPM, 12 mm orifice, solenoid coil 24 VDC (MG5, size 30 for more information, please refer to the section "Solenoid coils - Series F300").

Pneumatic symbol



Diagram



Construction characteristics

- Brass body and cover
 - AISI 303 stainless steel guide tube
 - AISI 430FR stainless steel mobile and fixed core
 - AISI 302 stainless steel springs
 - PBT piston
 - Sealing assemblies mainly PTFE, others FPM
- OPTIONS (on request):
- Chemical nickel plating
 - cULus certified solenoid coils

Technical characteristics


Maximum admitted pressure (bar)	100
Maximum fluid viscosity (mm²/s)	12cSt
Minimum differential pressure (bar)	3
Maximum admitted leakage (NL/h)	<0,2
Ambient temperature: with class F solenoid coil (°C)	-10 ... +55
Mounting position	Preferably with solenoid coil upwards



► Solenoid coil 30 mm Ø13, type MG



- Options:
 - Electrical connection via cables
 - Special voltages and powers
 - Self-extinguish




Ordering code	
MG	T
VOLTAGE	
4= 12 VDC	
5= 24 VDC	
56= 24 VAC (50-60 Hz)	
57= 110 VAC (50-60 Hz)	
58= 230 VAC (50-60 Hz)	
EAC	

► Solenoid coil 22 mm Ø10, type MI



- Options:
 - Electrical connection via cables
 - Special voltages and powers
 - Self-extinguish




Ordering code	
MI	T
VOLTAGE	
4= 12 VDC	
5= 24 VDC	
21= 48-50 VAC (50-60 Hz)	
56= 24 VAC (50-60 Hz)	
57= 110 VAC (50-60 Hz)	
58= 230 VAC (50-60 Hz)	
EAC	

► Solenoid coil 36 mm Ø13, type MK



- Options:
 - Electrical connection via cables
 - Special voltages and powers
 - Self-extinguish




Ordering code	
MK	T
VOLTAGE	
4= 12 VDC	
5= 24 VDC	
56= 24 VAC (50-60 Hz)	
57= 110 VAC (50-60 Hz)	
58= 230 VAC (50-60 Hz)	
EAC	

► Solenoid coil 30 mm Ø10, type XME



CE^{II 2 G Ex mb IIC T4 Gb}
CE^{II 2 D Ex mb IIIC T135°C Db IP65}



Ordering code	
XME	T-3
VOLTAGE	
5= 24 VDC	
56= 24 VAC (50-60 Hz)	
57= 110 VAC (50-60 Hz)	
58= 230 VAC (50-60 Hz)	
IECEx	

Operational characteristics

Class of insulation	Tolerance on AC voltage	Tolerance on DC voltage	IP Rating with connector	Continuous service	Electrical connection	Connector	Power		Weight (g)
	-10% ... +15%	±10%	IP65	ED100%	DIN 43650 A	Code: 300.11.00	AC (VA)	DC (W)	
H	-10% ... +15%	±10%	IP65	ED100%	DIN 43650 A	Code: 300.11.00	30	27	200

Series PVF

Angle seat valves with AISI 316 or 304 stainless steel body.

► 2-way angle seat valve. Threaded ports (Designed to prevent water hammer) - 1/2" ... 3"



II 2G Ex h IIC T4..T2 Gb X
II 2D Ex h IIIC T130°C..T230 Db X
-10°C≤Ta≤ +80°C




Table of dimensions

CODE	Φ= Function		G connection	Actuator (mm)	C (mm)	R (mm)	K (mm)	Q (mm)	T (mm)	A (mm)	L (mm)	SW (mm)	ℳ= Material	
	N.O.	N.C.											AISI	
PVF40F15-M	0	1	1/2"	40	50,5	27	111	1/8"	15	119	304	316	304	316
PVF50F15-M				50	60	33	124			131				
PVF50F20-M			3/4"	50	60	33	132	1/8"	16	140	75	32		
PVF50F25-M			1"	50	60	33	136	1/8"	17	145				
PVF63F25-M				63	75	41	162			169				
PVF63F32-M			1-1/4"	63	75	41	174	1/8"	21	187				
PVF90F32-M				90	106	55	223			235	116	50		
PVF63F40-M			1-1/2"	63	75	41	175	1/8"	21	187				
PVF90F40-M				90	106	55	223			235				
PVF63F50-M			2"	63	75	41	183	1/8"	22	201				
PVF90F50-M				90	106	55	232			250	138	69		
PVF125AF65-M			2-1/2"	125 (Aluminium)	148	74	302	1/4"	26	320	178	85		
PVF125AF80-M			3"	125 (Aluminium)	148	74	313	1/4"	27	372	210	100		

Technical data (N.O. - N.C. versions)

CODE	Φ= Function		G connection	KV (m³/h)	Actuator (mm)	Maximum ΔP (bar) (N.O.)		Maximum ΔP (bar) (N.C.)		Pilot pressure (bar)	ℳ= Material	
	N.O.	N.C.				Above seat	Under seat	Above seat	Under seat		AISI	
PVF40F15-M	0	1	1/2"	4,8	40	16	16	16	13	3 ... 8	304	316
PVF50F15-M				4,8	50	16	16	16	14			
PVF50F20-M			3/4"	10	50	12	16	16	14			
PVF50F25-M			1"	14	50	3	13	16	8			
PVF63F25-M				14	63	16	16	16	13			
PVF63F32-M			1-1/4"	23	63	14	13	16	6			
PVF90F32-M				23	90	/	/	16	16			
PVF63F40-M			1-1/2"	30	63	14	7	16	5			
PVF90F40-M				30	90	/	16	16	16			
PVF63F50-M			2"	70	63	6	5	9	3			
PVF90F50-M			2"	70	90	/	12	16	10			
PVF125AF65-M			2-1/2"	107	125 (Aluminium)	/	14	16	9			
PVF125AF80-M			3"	157	125 (Aluminium)	/	12	12	5	3 ... 10		

Pneumatic symbol



Construction characteristics				Technical characteristics (Valve body)				Technical characteristics (Actuator)			
<ul style="list-style-type: none"> - High flow rate thanks to body configuration with inclined seating - Anti water hammer functioning with input below poppet - Pneumatically operated valve with stainless steel body, resistant to ambient corrosion - Self-levelling poppet to ensure improved sealing - Optical position indicator - Self-adjusting maintenance free stuffer seals package - Valves may be mounted in all positions 				<ul style="list-style-type: none"> - Material: AISI 316/304 stainless steel - Fluid temperature: -10 °C ... + 180 °C - Ambient temperature: -10 °C ... + 80 °C - Fluid viscosity: max. 600cSt. - Poppet: PTFE - Seals package: PTFE and FKM 				<ul style="list-style-type: none"> - Body: AISI 304 - Pilot fluid: dry or lubricated air, gas and neutral fluids - Fluid temperature: max. +60 °C 			
OPTIONS (on request):											
<ul style="list-style-type: none"> - Double acting versions are available on request - Connection type: GAS ISO / NPT 											



► 2-way angle seat valve. Welded connection (Designed to prevent water hammer)



II 2G Ex h IIC T4..T2 Gb X
II 2D Ex h IIIC T130°C..T230 Db X
-10°C ≤ Ta ≤ +80°C




Table of dimensions

CODE	F = Function		Actuator (mm)	C (mm)	R (mm)	K (mm)	Q (mm)	HA (mm)	HL (mm)	DIN11850-2		DIN11850-3		M = Material	
	N.O.	N.C.								D	S	D	S	AISI 304	AISI 316
PVF40F15H-M	0	1	40	50,5	27	112	1/8"	118	70	19	1,5	20	2	A	B
PVF50F15H-M			50	60	33	125		128							
PVF50F20H-M			50	60	33	132		135	82	23					
PVF50F25H-M			50	60	33	136		150	100	29					
PVF63F25H-M			63	75	41	162		175							
PVF63F32H-M			63	75	41	174		186	125	35					
PVF90F32H-M			90	106	55	223		232							
PVF63F40H-M			63	75	41	175		190	130	41					
PVF90F40H-M			90	106	55	223		235							
PVF63F50H-M			63	75	41	183		206	155	53					
PVF90F50H-M			90	106	55	232		250							

Technical data (N.O. - N.C. versions)

CODE	F = Function		KV (m³/h)	Actuator (mm)	Maximum ΔP (bar) (N.O.)		Maximum ΔP (bar) (N.C.)		Pilot pressure (bar)	M = Material	
	N.O.	N.C.			Above seat	Under seat	Above seat	Under seat		AISI 304	AISI 316
PVF40F15H-M	0	1	4,8	40	16	16	16	13	3 ... 8	A	B
PVF50F15H-M			4,8	50	16	16	16	14			
PVF50F20H-M			10	50	12	16	16	14			
PVF50F25H-M			14	50	3	13	16	8			
PVF63F25H-M			14	63	16	16	16	13			
PVF63F32H-M			23	63	14	13	16	6			
PVF90F32H-M			23	90	/	/	16	16			
PVF63F40H-M			30	63	14	7	16	5			
PVF90F40H-M			30	90	/	16	16	16			
PVF63F50H-M			70	63	6	5	9	3			
PVF90F50H-M			70	90	/	12	16	10			

Pneumatic symbol



Construction characteristics	Technical characteristics (Valve body)	Technical characteristics (Actuator)
<ul style="list-style-type: none"> - High flow rate thanks to body configuration with inclined seating - Anti water hammer functioning with input below poppet - Pneumatically operated valve with stainless steel body, resistant to ambient corrosion - Self-leveling poppet to ensure improved sealing - Optical position indicator - Self-adjusting maintenance free stuffer seals package - Valves may be mounted in all positions <p>OPTIONS (on request):</p> <ul style="list-style-type: none"> - Double acting versions are available on request 	<ul style="list-style-type: none"> - Material: AISI 316/304 stainless steel - Fluid temperature: -10 °C ... +180 °C - Ambient temperature: -10 °C ... +80 °C - Fluid viscosity: max. 600cSt. - Poppet: PTFE - Seals package: PTFE and FKM 	<ul style="list-style-type: none"> - Body: AISI 304 - Pilot fluid: dry or lubricated air, gas and neutral fluids - Fluid temperature: max. +60 °C

► 2-way angle seat valve. Clamp ISO 2852 (Designed to prevent water hammer)



II 2G Ex h IIC T4..T2 Gb X
II 2D Ex h IIIC T130°C..T230 Db X
-10°C≤Ta≤ +80°C




Table of dimensions

CODE	Φ = Function		Actuator (mm)		A (mm)	K (mm)	Q (mm)	L (mm)	C (mm)	B (mm)	Ød	ØD	ℳ = Material	
	N.O.	N.C.											AISI 304	AISI 316
PVF40F15K-M	0	1		40	130	115	1/8"	80	19	27,5	15	34	A	B
PVF50F15K-M				50	140	126								
PVF50F20K-M				50	158	148								
PVF50F25K-M				50	165	140								
PVF63F25K-M				63	188	166								
PVF63F32K-M				63	200	174								
PVF90F32K-M				90	245	223								
PVF63F40K-M				63	210	175								
PVF90F40K-M				90	255	223								
PVF63F50K-M				63	221	185								
PVF90F50K-M				90	265	235								

Technical data (N.O. - N.C. versions)

CODE	Φ = Function		KV (m³/h)	Actuator (mm)	Maximum ΔP (bar) (N.O.)		Maximum ΔP (bar) (N.C.)		Pilot pressure (bar)	ℳ = Material	
	N.O.	N.C.			Above seat	Under seat	Above seat	Under seat		AISI 304	AISI 316
PVF40F15K-M	0	1	4,8	40	16	16	16	13	3 ... 8	A	B
PVF50F15K-M			4,8	50	16	16	16	14			
PVF50F20K-M			10	50	12	16	16	14			
PVF50F25K-M			14	50	3	13	16	8			
PVF63F25K-M			14	63	16	16	16	13			
PVF63F32K-M			23	63	14	13	16	6			
PVF90F32K-M			23	90	/	/	16	16			
PVF63F40K-M			30	63	14	7	16	5			
PVF90F40K-M			30	90	/	16	16	16			
PVF63F50K-M			70	63	6	5	9	3			
PVF90F50K-M			70	90	/	12	16	10			

Pneumatic symbol



Construction characteristics	Technical characteristics (Valve body)	Technical characteristics (Actuator)
<ul style="list-style-type: none"> - High flow rate thanks to body configuration with inclined seating - Anti water hammer functioning with input below poppet - Pneumatically operated valve with stainless steel body, resistant to ambient corrosion - Self-levelling poppet to ensure improved sealing - Optical position indicator - Self-adjusting maintenance free stuffer seals package - Valves may be mounted in all positions <p>OPTIONS (on request):</p> <ul style="list-style-type: none"> - Double acting versions are available on request 	<ul style="list-style-type: none"> - Material: AISI 316/304 stainless steel - Fluid temperature: -10 °C ... +180 °C - Ambient temperature: -10 °C ... +80 °C - Fluid viscosity: max. 600cSt. - Popet: PTFE - Seals package: PTFE and FKM 	<ul style="list-style-type: none"> - Body: AISI 304 - Pilot fluid: dry or lubricated air, gas and neutral fluids - Fluid temperature: max. +60 °C



II 2G Ex h IIC T4..T2 Gb X
II 2D Ex h IIIC T130°C..T°230 Db X
-10°C≤Ta≤ +80°C





Table of dimensions

CODE	F = Function		Actuator (mm)	C (mm)	R (mm)	K (mm)	Q (mm)	A (mm)	L (mm)	ASME - BPE				M = Material	
	N.A.	N.C.								ØD (mm)	ØB (mm)	Ød (mm)	ØH (mm)	AISI 304	AISI 316
PVF40F15J-M	0	1	40	50,5	27	127	1/8"	158	130	25	12,7	9,4	30	A	B
PVF50F15J-M			50	60	33	140		169							
PVF50F20J-M			50	60	33	138		172	150	25	19,05	15,75	30		
PVF50F25J-M			50	60	33	146		180							
PVF63F25J-M			63	75	41	169		205	160	50,5	25,4	22,1	30		
PVF63F40J-M			63	75	41	177		225							
PVF90F40J-M			90	106	55	225		267	200	50,5	38,1	34,8	30		
PVF63F50J-M			63	75	41	187		238							
PVF90F50J-M			90	106	55	235		280	230	64	50,8	47,5	30		

Technical data (N.O. - N.C. versions)

CODE	F = Function		KV (m³/h)	Actuator (mm)	Maximum ΔP (bar) (N.O.)		Maximum ΔP (bar) (N.C.)		Pilot pressure (bar)	M = Material	
	N.O.	N.C.			Above seat	Under seat	Above seat	Under seat		AISI 304	AISI 316
PVF40F15J-M	0	1	1,7	40	16	16	16	13	3 ... 8	A	B
PVF50F15J-M				50	16	16	16	14			
PVF50F20J-M			5,8	50	12	16	16	14			
PVF50F25J-M				50	3	13	16	8			
PVF63F25J-M			11,8	63	16	16	16	13			
PVF63F40J-M				63	14	7	16	5			
PVF90F40J-M			20,6	90	/	16	16	16			
PVF63F50J-M				63	6	5	9	3			
PVF90F50J-M			55,7	90	/	12	16	10			

Pneumatic symbol



Construction characteristics	Technical characteristics (Valve body)	Technical characteristics (Actuator)
<ul style="list-style-type: none"> - High flow rate thanks to body configuration with inclined seating - Anti water hammer functioning with input below poppet - Pneumatically operated valve with stainless steel body, resistant to ambient corrosion - Self-leveling poppet to ensure improved sealing - Optical position indicator - Self-adjusting maintenance free stuffer seals package - Valves may be mounted in all positions <p>OPTIONS (on request):</p> <ul style="list-style-type: none"> - Double acting versions are available on request 	<ul style="list-style-type: none"> - Material: AISI 316/304 stainless steel - Fluid temperature: -10 °C ... +180 °C - Ambient temperature: -10 °C ... +80 °C - Fluid viscosity: max. 600cSt. - Poppet: PTFE - Seals package: PTFE and FKM 	<ul style="list-style-type: none"> - Body: AISI 304 - Pilot fluid: dry or lubricated air, gas and neutral fluids - Fluid temperature: max. +60 °C

► 2-way angle seat valve. Flange mounting (Designed to prevent water hammer)



II 2G Ex h IIC T4..T2 Gb X
II 2D Ex h IIIC T130°C..T°230 Db X
-10°C≤Ta≤ +80°C




Table of dimensions

CODE	Φ= Function		Actuator (mm)		A (mm)	B (mm)	Q (mm)	L (mm)	C (mm)	H (mm)	ØE	N-OF	ØM	ØN	ØP	α	Ω= Material		
	N.O.	N.C.															AISI 304	AISI 316	
PVF40F15F-M	0	1			40	135	125	1/8"	130	2	14	65	4-14	16	45	95	45°	A	B
PVF50F15F-M					50	145	140												
PVF50F20F-M					50	165	140												
PVF50F25F-M					50	170	145												
PVF63F25F-M					63	190	175												
PVF63F32F-M					63	190	188												
PVF90F32F-M					90	230	235												
PVF63F40F-M					63	206	190												
PVF90F40F-M					90	250	240												
PVF63F50F-M					63	235	195												
PVF90F50F-M					90	277	245												

Technical data (N.O. - N.C. versions)

CODE	Φ= Function		KV (m³/h)	Actuator (mm)	Maximum ΔP (bar) (N.O.)		Maximum ΔP (bar) (N.C.)		Pilot pressure (bar)	Ω= Material	
	N.O.	N.C.			Above seat	Under seat	Above seat	Under seat		AISI 304	AISI 316
PVF40F15F-M	0	1	4,8	40	16	16	16	13	3 ... 8	A	B
PVF50F15F-M			4,8	50	16	16	16	14			
PVF50F20F-M			10	50	12	16	16	14			
PVF50F25F-M			14	50	3	13	16	8			
PVF63F25F-M			14	63	16	16	16	13			
PVF63F32F-M			23	63	14	13	16	6			
PVF90F32F-M			23	90	/	/	16	16			
PVF63F40F-M			30	63	14	7	16	5			
PVF90F40F-M			30	90	/	16	16	16			
PVF63F50F-M			70	63	6	5	9	3			
PVF90F50F-M			70	90	/	12	16	10			


Pneumatic symbol



Construction characteristics	Technical characteristics (Valve body)	Technical characteristics (Actuator)
<ul style="list-style-type: none"> - High flow rate thanks to body configuration with inclined seating - Anti water hammer functioning with input below poppet - Pneumatically operated valve with stainless steel body, resistant to ambient corrosion - Self-levelling poppet to ensure improved sealing - Optical position indicator - Self-adjusting maintenance free stuffer seals package - Valves may be mounted in all positions <p>OPTIONS (on request):</p> <ul style="list-style-type: none"> - Double acting versions are available on request 	<ul style="list-style-type: none"> - Material: AISI 316/304 stainless steel - Fluid temperature: -10 °C ... +180 °C - Ambient temperature: -10 °C ... +80 °C - Fluid viscosity: max. 600cSt. - Poppet: PTFE - Seals package: PTFE and FKM 	<ul style="list-style-type: none"> - Body: AISI 304 - Pilot fluid: dry or lubricated air, gas and neutral fluids - Fluid temperature: max. +60 °C



► Proximity sensor



Ordering code
PVF.01.S
● OUTPUT TYPE
01 = NPN (N.C.)
02 = NPN (N.O.)
03 = PNP (N.C.)
04 = PNP (N.O.)

Nickel brass sensor, usable on valves up to size 2 inches

for detection ON - OFF

Cable: 2 m

OPTIONS (on request):

A reduction is available for sizes 2 1/2" and 3".


Operational characteristics

Maximum current (mA)	Voltage field (VDC)	Temperature (°C)	Detection distance	IP Rating	Weight (g)
100	10 ... 30	-10 ... +70	3 mm (max) ±10%	IP67	69

Series PVA

Brass body angle seat valves and pad valve.

► "T" body version pad valve



Ordering code

PVA.B.A.P.T.C.M

A	ACTING
D	DE= Double acting
E	SC= Normally closed
F	SA= Normally open
G	PISTON
H	N= Non magnetic
I	M= Magnetic
J	CONNECTIONS
K	A= G1/4"
L	B= G3/8"
M	C= G1/2"
N	D= G3/4"
O	E= G1"
P	F= G1 1/4"
Q	G= G1 1/2"
R	H= G2"
S	SEALS
T	N= NBR
U	V= FPM
V	F= PTFE

Table of dimensions

Connection (N)	Non magnetic piston				Magnetic piston				G	H	L	M	P
	A	C	D	A	C	D	B	E					
G1/4"	93,5	77,5	41	97,5	81,5	45	16	10,25	32,5	28,5	64	47	25
G3/8"	93,5	77,5	41	97,5	81,5	45	16	10,25	32,5	28,5	64	47	25
G1/2"	93,5	78	41	99,5	82	45	17,5	10,25	32,5	28,5	68	47	30
G3/4"	105	83	41	113	90	48	22	11,25	44	40	79	70	36
G1"	117	89	41	125	101	53	28	11,25	44	40	94	70	44
G1 1/4"	131	103	48	136	108	53	28	11,25	44	40	110	70	55
G1 1/2"	154	118	57	166	130	69	36	13,75	56	49	120	90	60
G2"	169	124	57	181	136	69	45	13,75	56	49	140	90	73



Technical data

Actuator (Ø)	Valve (Ø)	Weight (g)
40	13,5	350
40	13,5	350
40	15	400
63	20,5	850
63	25	1100
63	30	1400
80	38	2100
80	49,5	3000



2-way valves, for interception of fluids, pneumatically actuated by a compact double or single acting cylinder with 360° swivel connections, NBR, FPM or PTFE seals in contact with the fluid. The barrel profile allows the use of magnetic sensors PNEUMAX code "1500_.", "RS_.", "RS_.", "HS_.", for sensor slot type "A" (see section 3, magnetic sensors series "SA" of the Pneumax General Catalogue).

Pressure curves


DOUBLE ACTING CYLINDER



SINGLE ACTING CYLINDER, NORMALLY CLOSED VALVE




SINGLE ACTING CYLINDER, NORMALLY OPEN VALVE



Construction characteristics	Technical characteristics
- Rear eye, piston and rod bushing: anodised aluminium - Cylinder: aluminium alloy anodised - Springs: zinc plated steel - Seals in contact with fluid: NBR, FPM, PTFE - Pneumatic cylinder seals: NBR, FPM, PTFE - Piston rod: chromed stainless steel - Bushing, bushing pad, nut pad: brass	Pneumatic cylinder fluid Valve fluid Working pressure (Cylinder) (bar) Temperature °C (Non magnetic piston, NBR seals) Temperature °C (Non magnetic piston, FPM seals) Temperature °C (Non magnetic piston, PTFE seals) Temperature °C (Magnetic piston, NBR, FPM, PTFE seals)
	Filtered air. No lubrication needed, if applied it shall be continuous
	Compatible fluid with seals compounds available
	10
	-10 ... +70
	-10 ... +150
	-10 ... +150
	-10 ... +70



► "Y" body version pad valve



Ordering code	
PVA.B.A.P.Y.C.M	
ACTING	
① DE = Double acting	
SC = Normally closed	
SA = Normally open	
PISTON	
② N = Non magnetic	
M = Magnetic	
CONNECTIONS	
A = G1/4"	
B = G3/8"	
C = G1/2"	
D = G3/4"	
E = G1"	
F = G1 1/4"	
G = G1 1/2"	
H = G2"	
SEALS	
N = NBR	
V = FPM	
F = PTFE	



Table of dimensions

Connection (N)	Non magnetic piston					Magnetic piston					B	E	F	G	H	L	M	P	R	T
	A	C	D	Q	S	A	C	D	Q	S										
G1/4"	121	71	45	95	51	124	74	48	97	53	50	10,3	G1/8"	32,5	28,5	52	47	21	10,5	50
G3/8"	121	71	45	95	51	124	74	48	97	53	50	10,3		32,5	28,5	52	47	21	10,5	50
G1/2"	127	71	45	97	54	130	74	48	99	56	56	10,3		32,5	28,5	57	47	27	13,5	56
G3/4"	148	80	48	119	66	201	133	104	175	92	68	11,3		44	40	70	70	32	16	66
G1"	159	75	48	123	75	215	131	104	175	92	84	11,3		44	40	82	70	38	19	78
G1 1/4"	184	91	65	140	70	231	138	112	172	96	93	11,3		44	40	105	70	47	23,5	101
G1 1/2"	180	99	81	173	85	255	129	111	187	107	126	13,8		56	49	125	90	55	27,5	113
G2"	246	106	88	182	88	269	129	111	203	109	140	13,8		56	49	136	90	68	34	125


2-way valves, for interception of fluids, pneumatically actuated by a compact double or single acting cylinder with 360° swivel connections, NBR, FPM or PTFE seals in contact with the fluid. The barrel profile allows the use of magnetic sensors PNEUMAX code "1500_," "RS_," "RS_," "HS_," for sensor slot type "A" (see section 3, magnetic sensors series "SA" of the Pneumax General Catalogue).

Pressure curves


DOUBLE ACTING CYLINDER



SINGLE ACTING CYLINDER, NORMALLY CLOSED VALVE



SINGLE ACTING CYLINDER, NORMALLY OPEN VALVE



Construction characteristics

- Rear eye, piston and rod bushing: anodised aluminium
- Cylinder: aluminium alloy anodised
- Springs: zinc plated steel
- Seals in contact with fluid: NBR, FPM, PTFE
- Pneumatic cylinder seals: NBR, FPM, PTFE
- Piston rod: chromed stainless steel
- Bushing, bushing pad, nut pad: brass

Technical characteristics

Pneumatic cylinder fluid	Filtered air. No lubrication needed, if applied it shall be continuous
Valve fluid	Compatible fluid with seals compounds available
Working pressure (Cylinder) (bar)	10
Temperature °C (Non magnetic piston, NBR seals)	-10 ... +70
Temperature °C (Non magnetic piston, FPM seals)	-10 ... +150
Temperature °C (Non magnetic piston, PTFE seals)	-10 ... +150
Temperature °C (Magnetic piston, NBR, FPM, PTFE seals)	-10 ... +70



HEADQUARTERS



PNEUMAX S.P.A.

Via Cascina Barbellina, 10
24050 Lurano (BG) - Italia
Tel. 035/4192777
Fax 035/4192740 - 035/4192741
info@pneumaxspa.com
www.pneumaxspa.com

WORLDWIDE NETWORK

EUROPE

ALBANIA

Industrial Air Solution shpk
Rruga industriale Tirane Vore, km 11,
1032 Vore Tirane
Tel. +355 69 40 80 349
info@iasolution.al
www.iasolution.al

AUSTRIA AND SWITZERLAND

Managed by Pneumax GmbH (Germany)

BELGIUM

Pneuvano BV
Korallenhoeve 4
2160, Wommelgem
Tel. +32 3 355 32 20
info@pneuvano.com
www.pneuvano.com

BULGARIA

Ulmer DM OOD
Adam Mizkevich Str. 4a, 1360, Sofia
Tel. +359 (2) 9259951
office@ulmer.bg
www.ulmer.bg

CYPRUS

G C V Spare Parts & Services Ltd
Industrial Area, Anatoniko 8086
P.O. Box 62731, Paphos
Tel. +357 26812444
gcv.cy@cyanet.com.cy
www.gcv-parts.com

CROATIA

ProElektronika d.o.o. - Zagabria
Stefanovecka 10, 10040, Zagabria
Tel. +385 (0) 1 5588 988
info@proelektronika.hr
www.proelektronika.hr

ESTONIA

Alas-Kuul AS
Loomäe tee 1, Lehmja küla
75306, Rae vald Harjumaa
Tel. +372 6593 218
info@alas-kuul.ee
www.alas-kuul.ee

FRANCE

Pneumax France SAS
Z.I. NORD PARADIES 7
Rue de Waldkirch - BP 42
67601, Selestat CEDEX
Tel. +33 (3) 88580450
commercial@pneumax-france.fr
www.pneumax-france.fr

GERMANY

Pneumax GmbH
Tantalstraße 4
63571, Gelnhausen
Tel. +49 (0) 6051 9777 0
info@pneumax-gmbh.de
www.pneumax.de

GREECE

Hydropneumatic Hellas S.A.
69, Spirou Patsi Str. T.K., 118 55, Atene
Tel. +30 (210) 3474181-2-3
info@mitsis.com.gr
www.mitsis.com.gr

UNITED KINGDOM

Pneumax UK Ltd.
110 Vista Park,
Mauretania Road
SO16 0YS, Nursling
Tel. +44 2380 740412
sales@pneumax.co.uk
www.pneumax.co.uk

ICELAND

Barki E.H.F. Ltd
Nybylavegi 22, 200, Kópavogur
Tel. +354 554 6499
barkiea@islandia.is

LITHUANIA

UAB "Domingos prekyba"
Savanorių PR 187-4 Korp, 2053, Vilnius
Tel. +370 5 2322231
info@dominga.lt
www.dominga.lt

NORTHERN MACEDONIA

DIL KOM DOOEL
St. Joska Jordanoski No 657500, Prilep
Tel. +389 78244177
export.dilkom@gmail.com
www.dilkom.mk

MALTA

iAutomate Limited
San Bernard, Marsa MRS 1332, Malta
Tel. +356 2786 3996
matthew@iautomate.mt
www.iautomate.mt

NETHERLANDS

Pneu/Tec B.V.
Dirk Storklaan 75, 2132 PX, Hoofddorp
Tel. +31 (0) 235699090
sales@pneutec.nl
www.pneutec.nl

POLAND

Rectus Polska SP. Z.O.O.
Gumna 96, 43-426, Debowiec
Tel. +48 (33) 857 98 00
pneumax@pneumax.pl
www.pneumax.pl

PORTUGAL

Portugal Pneumax Lda
Complexo Industrial da
Granja Fracção H-Casarias
2625-607, Vialonga
Tel. +351 (219) 737390
geral@pneumax.pt
www.pneumax.pt

CZECH REPUBLIC

Pneumax Automation s.r.o.
U Panského mlýna 240/9,
747 06, Opava
Tel. +420 553 760 953
pneumax@pneumaxsro.cz
www.pneumaxsro.cz

ROMANIA

Gica Import Export
Zona Industriala de Vest str. II nr. 5,
310491, Arad
Tel. +40 257 259816
comercial@gica.ro
www.gica.ro





Pneumax Fluid Control Catalogue

DENMARK - FINLAND NORWAY - SWEDEN (SCANDINAVIA)

Pneumax Scandinavia AB
Strandvägen 101, SE-234 31, Lomma
Tel. +46 (40) 617 40 40
info@pneumax.se
www.pneumax.se

SERBIA
Hidraulika DOO
Cirila i Metodija 15, 15000, Šabac
Tel. +381 15 360 090
info@hidraulika.rs
www.hidraulika.rs

SLOVENIA
Hidravlika d.o.o.
Medlog, 16, 3000, Celje
Tel. +386 (0) 5453610
info@hidravlika.si
www.hidravlika.si

TRG d.o.o.
Celovška cesta 150, 1000, Ljubljana
+386 1 500 14 51
info@podjetje-trg.si
www.podjetje-trg.si

SPAIN
Pneumax S.A.
Olaso Kalea, 54, 20870, Elgoibar
Tel. +34 943 744144
pneumax@pneumax.es
www.pneumax.es

Pneumax Catalunya S.A.
C/Riera de Vallvidrera,
Parc. 2N. 1 Pl. Riera del Moli
8750, Molins de Rei
Tel. +34 (93) 680 25 30
pneumax@pneumaxcat.com
www.pneumax.es

TURKEY
Eteknik Otomasyon Tic. Ltd. Sti
Perpa Ticaret Merkezi B Blok Kat:11 No:1636 Okmeydani Sisli (İstanbul)
Tel. +90 212 320 81 10
recepakar@eteknik.com
www.eteknik.com

UKRAINE
UKRTECHTRONIC LLC.
st. Nyzhnoyurkivska, 9, 04080, Kiev
Tel. +38 044 500 98 48
sales@techtronic.com.ua
www.techtronic.com.ua

HUNGARY
Szele-Tech Bt.
Gyárdányi u. 33-39. I. em. 108., 1141, Budapest
Tel. +36 1 401 0023
info@szele-tech.hu
www.szele-tech.hu



NORTH AMERICA

CANADA

Manufacture Scorpion Inc.
561, rue Edouard, J2G 3Z5, Granby
Tel. +1 (450) 378-3595
contact@mscorpion.com
www.manufacturescorpion.com

USA

Pneumax Automation LLC
128 Durkee Lane, Dallas
NC 28034 - USA
Tel.: +1 704 215 6991
Fax: +1 888 613 6529
info@pneumax.us
www.pneumax.us



MEXICO

Pneumatecnia S.A. DE C.V. - Zapopan
Calle Volcán Popocatépetl 1844, Colli Urbano
45070, Zapopan, Jalisco
Tel. +52 33 31 255978
pneumatecnia@yahoo.com.mx
www.pneumatecnia.com.mx

CENTRAL AMERICA

COSTA RICA

PYASA Proyectos y Automatizacion S.A.
Oficentro Santa María Oficina 1A,
50 metros Norte
Del Hampton Inn & Suites, Alajuela
Tel. +506 2441-5129 / 2441-5130
info@pyasa.net
<https://pyasa.net>



EL SALVADOR

Tecni Equipos S.A. de C.V.
Av. Sierra Nevada, 704 Edificio CC, 2
Colonia Miramonte, San Salvador
Tel. (503) 2260-8293
Tel. (503) 2261-1497
tecniequipos.com.sv



GUATEMALA

PYASA Proyectos y Automatización S.A.
Avenida 3era 13-30 El Rosario Ofibodega
San Javier zona 3 de Mixco bodega 7
Città del Guatemala
Tel. +502 24911414
info@pyasa.net
<https://pyasa.net>

NICARAGUA

PYASA Proyectos y Automatización S.A.
Plaza Maranhao, local 7, Reparto Los Robles, o
bien, del Hotel Seminole 100 m sur,
1/2 m al oeste
Managua
Tel. +505-2255-6840
info@pyasa.net
<https://pyasa.net>

SOUTH AMERICA

ARGENTINA

Figli Daniele S.r.l.
PTE PERON 3234
San Justo - Pcia De Bs As.
Tel. +54 11 4484-2074
Fax +54 11 4651-6721
bruno@dinautomacion.com.ar
www.dinautomacion.com.ar



BRAZIL

Pneumax Brasil
Rua Apucarana 211
83010-050, São José dos Pinhais
Tel. +55 41 33987262
diretoria@pneumaxbr.com.br
www.pneumaxbr.com.br

CHILE

Schultz Automatizacion e Ingenieria Ltda
El Retiro 21 - Enea - Pudahuel, Santiago
Tel. +56 (2) 4951400
jschultz@schultzautomatizacion.cl
www.schultza.cl

COLOMBIA

Soluciones Neumaticas S.A.S.
Calle. 21 #1-21, Barrio San Nicolas, Cali
Tel. +57 (2) 4897647
ingenieria@solucionesneumaticas.com
www.solucionesneumaticas.com

ECUADOR

Equipos para automatización Industrial Equipautind S.A.
Km 12,5 de la vía a Daule s/n entre
La Ciudadela el caracol y el motel las Palmas
090706, Guayaquil
Tel. +593-42017785 / 2017914
info@equipautind.com.ec
www.equipautind.com.ec

AINSA S.A.

Av. Juan Tanca Marengo
Km 2,5 y Agustín Freire
EC090509, Guayaquil
Tel. +593-4 3712670
info@ainsa.com.ec
www.ainsa.com.ec

PERU

Neumatec Perù S.A.C.
Calle General Suárez 1023,
Miraflores, Lima 18
Tel. +51 (1) 4442499
ventas@neumatecperu.com
www.neumatecperu.com

WEF Perù S.A.C.

Jr. Dinamarca 1427,
LIMA 01, Cercado de Lima
Tel. +511 4255740
oficinalcentral@wefperu.com
www.wefperu.com

URUGUAY

Secoin S.A
General Aguilar 1270 bis,
Gral. Fausto Aguilar 1270,
11800 Departamento de Montevideo
Tel. +598 2209 3815
ventas@secoin.com.uy
www.secoin.com.uy

VENEZUELA

Sinteco Barquisimento
AV.Las Industrias Km2,
Edif. Centro de servicios
mercantiles local 2, Barquisimeto
Tel. +58 414 3500587
sintecobarqto@gmail.com



AFRICA

ALGERIA

C.M.P.R. Sarl
23 Rue Lalla Fatma N'Soumer Hassen
Badi El-Harrach, Algeri
Tel. +213 21 82 70 69
tn.cmpr@yahoo.fr

EGYPT

Egyptian Engineering
Shop 6 building no 1 Jordan co.
10th Of Ramadan City
Tel. +20554368385
Fax: +20554368385
info@eefhydropneu.com
www.eefhydropneu.com

ALKHAMIS Hydraulic Company

A/6 Elfaroqia Buildings -Gesr
El Suis St., El Nozha Cairo
Tel. +20 2 26206391/3/2
Fax: +20 2 26206394
gkhamisimp@gmail.com
www.alkhamis-eg.com

GHANA

Cemix Limited
34 SPINTEX ROAD-ACCRA-GHANA-WEST
Tel. +233 0302 817030
sales@cemixghana.com
www.cemixghana.com

MOROCCO

R2i TFZ
Ilot 87, 1er étage, Bureau 20,
zone franche d'Exportation Tanger
Tel. +212 539 39 10 17
r2itfz@r2imaroc.ma
www.r2itfz.com

TUNISIA

L'Equipement moderne
86, Av. de Carthage, 1000, Tunisie
Tel. +216 71 343844
equipement.moderne@planet.tn
www.equipementmoderne.com.tn

ASIA

SAUDI ARABIA

Arabian Universal Establishment for Trading
Southern Shopping Center, P.O BOX 3105
21471, Jeddah
Tel. +966 26 477159
bassam@aue-co.com
www.arabianuniversal.com

CHINA

Pneumax Pneumatic
Equipments Co., Ltd.
No. 76, Jinma Rd., Jiufu Economic
Development Zone, Jiuting Town
201615, PRC, Shanghai
Tel. +86 (21) 57763100
sales@pneumaxchina.com
www.pneumaxchina.com



UNITED ARAB EMIRATES

Fine Industrial & Agri ENG. Services
P. O. BOX 5763, Sharja UAE
Tel. +971 (6) 5335434
fineinds@emirates.net.ae

PHILIPPINES

**Integrated Hydro-Pneumatic
Systems, Inc.**
N°4 St. Thomas Avenue,
Lopez Commercial Area
Sucat, Parañaque City
Tel. +632 02 820-0569
integhps@iconex.net

JORDAN

Al Sultan Company
P.O. Box 620996
11162, Amman
Tel: + 962 6 4753764
info@alsultanco.com
www.alsultanco.com

INDIA

Pneumax Pneumatic
India Pvt. Ltd.
D-82, Hosiery Complex, Phase-II extn.
201305, Noida, UP
Tel. +91 (120) 4352560 / 61 / 62
info@pneumax-india.com
www.pneumaxindia.com



INDONESIA

Managed by Pneumax Singapore Pte Ltd

PT. Mutiara Citramulia Teknindo
Ruko Karawaci Residence Blok A1,
No. 17 Jl. Raya
Legok. Bojong Nangka Kelapa Dua
Serpong-Tangerang 15810, Banten, 15810,
Giacarta
Tel. +62 21 29324792
pneumaxmct@cbn.net.id
www.pneumaxspa.com/en

IRAN

Ital Electro Pneumatic
NO. 204-2ND FLOOR-TAGHINIA
BLDG-SOUTH SA'ADI STREET
114715719, Teheran
Tel. +98 (21) 33919177
info@italpneum.com

ISRAEL

Ilan & Gavish
Yokneam Ilit 20692
POB 335, Soltam Site
Tel. +972 3 9221824
mail@ilan-gavish.com
www.ilan-gavish.co.il

LEBANON

Yammine Trading Company SARL
Boushrieh, Industrial City, P.O. Box 90 684
Jdeideh, El Metn 1202
2060, Beirut
Tel. +961 1 885520
info@yamminetrading.com
www.yamminetrading.com

MALAYSIA

Managed by Pneumax Singapore Pte Ltd

PSI Pneumatic Control Sdn Bhd
4M (1) Desa Universiti Commercial Complex,
Jalan Sungai Dua
11700, Penang
Tel. +60 4 6592627
sales-psi@airdynamics.com.sg

OMAN

Muscat Pneumatic System & Project LLC
Shop # 1484, Building # 1450B,
P.O. Box 105 PC: 120,
Muscat, Sultanate Of Oman
Tel. +968 93989398
sales@muscat-pneumatic.com

PAKISTAN

Fluid Tekhnik
Suite 101-104 Industrial Town Plaza, Opp. Sind
Madressah, Shahrah-e-Liaquat
74000, Karachi
Tel. +92 (21) 2410335
info@fluid-teknik.com.pk
www.fluid-teknik.com.pk

SINGAPORE

Pneumax Singapore Pte Ltd
51, Ubi Avenue 1/01-16,
Paya Ubi Industrial Park
408933, Singapore
Tel. +65 6392 0581
sales@pneumax.com.sg
www.pneumax.com.sg



SYRIA

Al Rowad Trading
P.O. BOX. 12806
Damasco
Tel: +963 944 228 955
alrowadtrading01@hotmail.com

THAILAND

Thai Agency Engineering Co. LTD
9 Soi Yasoop 2, 2nd-3rd Floor,Vorasin
building,Vipavadirangsit Road,Ladyao
10900, Chumphon
Tel: +66 (2) 6915900
taec@bkk.loxinfo.co.th
www.thai-a.com

OCEANIA

AUSTRALIA

Air Automation Group Pty Ltd
15 Broadhurst Rd,
Ingleburn NSW 2565
Tel. +61 02 9618 6777
sales@airautomation.com.au
www.airautomation.com.au

NEW ZEALAND

Treotham Automation Pty Ltd
Level 4, 21 Putney Way,
Manukau Auckland 2104
Tel. +64 9278 6577
Fax: +64 9278 6578
info@treotham.co.nz
www.treotham.co.nz

www.pneumaxspa.com



PNEUMAX

PNEUMAX S.p.A.

Via Cascina Barbellina, 10
24050 Lurano (BG) - Italy
P. +39 035 41 92 777
info@pneumaxspa.com
www.pneumaxspa.com